Inspect Minnesota & Midwest Soil Testing

P.O. Box 10853 White Bear Lake, MN 55110 651-492-7550/Brian@Midwestsoiltesting.com

Brian Humpal

MPCA Licensed Advanced Inspector

SUBSURFACE SEWAGE TREATMENT SYSTEM (SSTS) COMPLIANCE REPORT

Inspection Address: 10281 Hadley Ave N, Grant, MN 55110

REPORT SUMMARY

I have performed an "MPCA Compliance Inspection" on this system and have reviewed the original design/permit records, along with a previous compliance inspection from 2014, which were on file at Washington County. This system consists of two pre-cast septic tanks, a pre-cast lift tank, and a rock trench drainfield. It should be noted that the septic tanks are currently due for maintenance pumping and should be pumped when possible.

Predicated on my inspection of the system and my review of the records, it is my opinion that this system <u>presently meets</u> MPCA minimum compliance inspection requirements.

Inspect Minnesota and Midwest Soil Testing have been hired to perform a compliance inspection of this SSTS for compliance with local ordinances pursuant to Minn. Stat. § 115.55 (2013). This compliance inspection covers only the criteria required by Minn. Stat. § 115.55 Subd. 5a (2013) and Minn. R. 7080.1500 (2011). A compliance inspection is an indication of the current compliance status of the system and does not guarantee the performance or longevity of this system beyond the date of inspection, as it is impossible to determine the future performance of any system. Inspect Minnesota and Midwest Soil Testing disclaim any use of this compliance inspection beyond determining SSTS compliance pursuant to Minn. Stat. § 115.55 Subd. 5a (2013) and Minn. R. 7080.1500 (2011).

Please contact me should you have any questions.

Brian Humpal
Brian Humpal



Compliance Inspection Form

Existing Subsurface Sewage Treatment Systems (SSTS)

Doc Type: Compliance and Enforcement

Instructions: Inspection results based on Minnesota Pollution Control Ager requirements and attached forms – additional local requirements may also a									
Submit completed form to Local Unit of Government (LUG) and syste within 15 days	m owner								
System Status									
System status on date (mm/dd/yyyy): _8/10/2017									
	Noncompliant – Notice of Noncompliance (See Upgrade Requirements on page 3)								
Reason(s) for noncompliance (check all applicable)									
☐ Impact on Public Health (Compliance Component #1) – Immi	nent threat to public health and safety								
☐ Other Compliance Conditions (Compliance Component #3) –	Imminent threat to public health and safety								
☐ Tank Integrity (Compliance Component #2) – Failing to protect	et groundwater								
Other Compliance Conditions (Compliance Component #3) –									
☐ Soil Separation (Compliance Component #4) – Failing to prot									
Operating permit/monitoring plan requirements (Compliance C	component #5) – Noncompilant								
Property Information Parcel ID# or S	ec/Twp/Range:								
Property address: _10281 Hadley Ave N, Grant, MN 55110	Reason for inspection: Property Transfer								
Property owner: Neal Hoffoss	Owner's phone:								
Or	D 440 770 7050								
Owner's representative: Thad Rich (Re/Max)	Representative phone: 612-770-7653								
Local regulatory authority: Washington County Prior system description: Two pre-sest centre tanks a pre-sest lift tank.	Regulatory authority phone: 651-430-4052								
Brief system description:	and a rock trench drainneid.								
Comments of recommendations.									
Certification									
I hereby certify that all the necessary information has been gathered to de determination of future system performance has been nor can be made du possible abuse of the system, inadequate maintenance, or future water us	e to unknown conditions during system construction,								
Inspector name: Brian Humpal	Certification number: L5342								
Business name: Inspect Minnesota, Midwest Soil Testing	License number: L2896								
Inspector signature: Brian Humpal	Phone number: 651-492-7550								
Necessary or Locally Required Attachments									
Soil boring logs	Forms per local ordinance								
☑ Other information (list): Report Summary, Property Information, Di	sclaimer, License								

www.pca.state.mn.us • 651-296-6300 • 800-657-3864 • TTY 651-282-5332 or 800-657-3864 • Available in alternative formats wq-wwists4-31 • 1/24/12 Page 1 of 3

Property address: _ 10281 Hadley Ave N, Grant, MN 55110

Inspector initials/Date: 08/10/2017

1.	lm	Impact on Public Health – Compliance component #1 of 5				
	Co	ompliance criteria:			Verification method(s):	
		stem discharge sewage to the bund surface.	☐ Yes	⊠ No	 Searched for surface outlet Searched for seeping in yard/backup in home 	
		stem discharge sewage to drain tile surface waters.	☐ Yes	⊠ No	 ☑ Excessive ponding in soil system/D-boxes ☐ Homeowner testimony (See Comments/Explanation) ☑ "Block soil" share soil dispersed system 	
		rstem cause sewage backup into religion restablishment.	☐ Yes	⊠ No	 ☐ "Black soil" above soil dispersal system ☐ System requires "emergency" pumping ☐ Performed dye test 	
		ny "yes" answer above indicates I Imminent Threat to Public Heal			☐ Unable to verify (See Comments/Explanation) ☐ Other methods not listed (See Comments/Explanation)	
	Сс	omments/Explanation:				
2.		soil boring over the drainfield indicated ank Integrity – Compliance com	-		Ngray solis.	
	Compliance criteria:			Verification method(s):		
		stem consists of a seepage pit, sspool, drywell, or leaching pit.	☐ Yes	⊠ No	☑ Probed tank(s) bottom☑ Examined construction records	
		epage pits meeting 7080.2550 may be mpliant if allowed in local ordinance.			Examined Tank Integrity Form (Attach)Observed liquid level below operating depth	
		ewage tank(s) leak below their signed operating depth.	☐ Yes	⊠ No	☐ Examined empty (pumped) tanks(s) ☐ Probed outside tank(s) for "black soil"	
		yes, which sewage tank(s) leaks:			☐ Unable to verify (See Comments/Explanation)	
		ny "yes" answer above indica ⁄stem is Failing to Protect Gro		ter.	☐ Other methods not listed (See Comments/Explanation)	
3.	Lo Lif	omments/Explanation: wered underwater camera into tanks - it pump and alarm were operational at ther Compliance Conditions	the time of	f the inpsection.	nt #3 of 5	
	a.	Maintenance hole covers are damaged	d, cracked,	unsecured, or app	ear to structurally unsound. ☐ Yes* ☒ No ☐ Unknown	
	b.	Other issues (electrical hazards, etc.) to in *System is an imminent threat to put			pact public health or safety. ☐ Yes* ☒ No ☐ Unknown	
		Explain:				
	c.	System is non-protective of ground wa *System is failing to protect ground Explain:		er conditions as det	ermined by inspector ☐ Yes* ☒ No	

www.pca.state.mn.us • 651-296-6300 • 800-657-3864 • TTY 651-282-5332 or 800-657-3864 • Available in alternative formats wq-wwists4-31 • 1/24/12 Page 2 of 3

Property address: 10281 Hadley Ave N, Grant, MN 55110

Inspector initials/Date: 08/10/2017

Date of installation: 2003	Unkr	nown	Verification r	nethod(s):		
Shoreland/Wellhead protection/Food Beverage Lodging?		□No	Soil observation	n does not expire. Pr		
Compliance criteria:			unless site con	observations by two independent parties are sufficient unless site conditions have been altered or local		
For systems built prior to April 1, 1996, and not located in Shoreland or Wellhead Protection Area or not serving a food, beverage or lodging establishment:	requirements differ. In Shoreland or Wellhead Area or not serving a food, or lodging establishment: In as at least a two-foot vertical distance from periodically Yes		soil observation(s) (Attac	observation(s) (Attach boring logs) erifications (Attach boring logs) (Holding tank(s), no drainfield)		
Drainfield has at least a two-foot vertical separation distance from periodically saturated soil or bedrock.				Unable to verify (See Comments/Explanation)		
Non-performance systems built April 1,	⊠ Yes	□ No	Comments/Exp	lanation:		
1996, or later or for non-performance systems located in Shoreland or Wellhead			reviewed previous	reviewed previous compliance inspection from 2014.		
Protection Areas or serving a food, beverage, or lodging establishment:			Reviewed design	gn and permit records	S.	
Drainfield has a three-foot vertical separation distance from periodically saturated soil or bedrock.*						
"Experimental", "Other", or "Performance"	☐ Yes ☐	□No	Indicate dept	hs of elevations		
systems built under pre-2008 Rules; Type IV or V systems built under 2008 Rules (7080. 2350 or 7080.2400 (Advanced Inspector License required)			A. Bottom of dist	tribution media	See Attached Boring Log(s)	
Drainfield meets the designed vertical			B. Periodically s	aturated soil/bedrock		
separation distance from periodically saturated soil or bedrock.			C. System separ	ation		
Any "no" answer above indicates the	he syst	em is	-	npliance separation*		
Failing to Protect Groundwater.	ic syst		^May be reduce Ordinance.	ed up to 15 percent if	allowed by Local	
Operating Permit and Nitrogen B	MP* – C		•	f 5 🛛 Not appl	icable	
Is the system operated under an Operating Peri			_	below is required		
Is the system required to employ a Nitrogen BM		☐ Yes [-	below is required		
BMP=Best Management Practice(s) specifi	ed in the	system des	ign			
If the answer to both questions is "no",	this sec	tion does	not need to be d	completed.		
Compliance criteria						
a. Operating Permit number:				No		
Have the Operating Permit requirements to	een met	?	☐ Yes ☐			
b. Is the required nitrogen BMP in place and	☐ Yes ☐	No				

Upgrade Requirements (Minn. Stat. § 115.55) An imminent threat to public health and safety (ITPHS) must be upgraded, replaced, or its use discontinued within ten months of receipt of this notice or within a shorter period if required by local ordinance. If the system is failing to protect ground water, the system must be upgraded, replaced, or its use discontinued within the time required by local ordinance. If an existing system is not failing as defined in law, and has at least two feet of design soil separation, then the system need not be upgraded, repaired, replaced, or its use discontinued, notwithstanding any local ordinance that is more strict. This provision does not apply to systems in shoreland areas, Wellhead Protection Areas, or those used in connection with food, beverage, and lodging establishments as defined in law.


www.pca.state.mn.us • 651-296-6300 • 800-657-3864 wq-wwists4-31 • 1/24/12 Page 3 of 3

<u>Inspect Minnesota & Midwest Soil Testing</u> Subsurface Sewage Treatment System Owner/Property Information

This information will be used for the purpose of conducting an MPCA Compliance Inspection

This information will be used for the purpose of conducting an MPCA	A Compliance Inspection.				
Date of Inspection: August 10, 2017	Time: 9:30 AM				
Property Address: 10281 Hadley Ave N, Grant, MN Zip: 55110					
Property Owner: Neal Hoffoss	Phone:				
Tank(s) Tank(s)Material Soil Treatment System Septic 2 Fiberglass Rock trench Aerobic Plastic Gravelless trench Lift Metal Chamber trench Holding Concrete Seepage bed Other: Block Mound Other At-grade	Other Alternative system Experimental system Cesspool system Other system				
Are the tank maintenance covers accessible? ☐ Yes ☒ No *If	no, proper maintenance must be				
performed through the maintenance holes. Maintenance hole cover					
the ground surface to facilitate access and proper maintenance of					
Year house built: 1967 Year septic installed: 2003	Tank size (gals.): 2-1000				
<u>_</u>	sidents in home? 1-2				
Number of bedrooms? 3 Are all floors drained by g	ravity? Y				
Garbage disposal? Y Whirlpool bath?					
More than one system (laundry, etc.)? N					
Does this property have any footing drain tiles connected to the septic system? N					
Are any buildings on this property such as garages or out-building Drain in garage, point of dishcarge unknown.	gs connected to this system?				
Are there any additional systems on this property serving other bu	ildings? N				
Location of septic system on lot? North Side					
Location of water well on lot? West Side Is the well a deep well? Y					
Have you ever experienced any problems with the system such as	: tree roots, sewage back-ups,				
surfacing of sewage onto the ground, septic tank overflowing, etc.	; or have any repairs been made				
to the system? N If yes, explain:					
When was the system last pumped? Unknown Name of pum	iner:				
How often pumped in previous years? Due For Pump Is system on a monitoring plan? N					
Have you received notices from any government agency concerning this system? N Is your property located in a shoreland management area? Y					
Do you have any additional information that should be given to the	e new owner? N				
I hereby certify that the above information is correct to the best of my knowledge. I also understand that if the system is considered "non-compliant/failing" per MPCA rules, that the inspector must by law submit a copy of this report to the local government unit within 15 days of the date of inspection completion. I also agree that unless otherwise noted in					

this report, that I/we are ultimately responsible for payment of all fees for all work performed relative to this inspection by Inspect Minnesota and Midwest Soil Testing.



Log Of Soil Borings

Location of Project: 10281 Hadley Ave N, Grant, MN 55110					
Borings Made By: Inspect Minnesota				Date:	10/2/14
Auger Used: Hand/Bucket		Classification System: USDA		USDA	
Boring Number: 1		Boring Number:			
Surface		96.70'	Surface		
Elevation of	Benchmark =	100.00' concrete door	Elevation	of	
Boring	threshold at b	asment service door	Boring		
Depth In	Soils Fr	ncountered	Depth In	Soils F	ncountered
Inches			Inches	20110 121	Ticouritei eu
0-6 6-37 37-68	7.5YR 3/4 10YR 3/4 Sa Gravel Refus	2.5/2 Loam Loamy Sand Andy Loam With Cobbles Cobs At 68"			
93.95' Elevation To Bottom Of Drainfield			Elevation To Bottor		
-91.03' Depth To Redox Or End Of Boring =2.92'/35" Of Separation			Depth To Redox Or Of Separation	End Of Boring	
-2.32/33 Of Separation			Or Separation		
End Of Boring At: 68"				End Of Boring At:	
Redox Present At: None				Redox Present At:	
Standing Water Present At: None			Standing	Water Present At:	

Bottom Of Distribution Medium At: 33" Or Elevation 93.95' At Soil Probe

	, ———	Soll Bor	Δ	3-31
Locatio	on or Project 10201	naley	are. N'	
	made by	V	Date	4-12-03
Classif	fication System: AASHO; USDA	-scs 🗶	; Unified	_; other,
	used (check two): Hand 📐, or Pow			
			,	
Depth,	Boring number	Depth,	Boring number	b-2
in	Surface elevation 498-00' B.M. = 1000-00, LOWER ENTRY	in	Surface eleve	11 945.60
feet	B.M' = 1000.00, LOWER ENTRY	feet	}	
o 	0-8" LOAMY SAND	0	0-8 60	AMYSAND
	16 YR 2/2 V.OK. BRN.			2 V.DK.GR.BRN.
1 —		1 —	9-42"	
	0-3011		0-32	14 D.YL.BRN.
2 —	10 4R 3/3 DK.BRW.	2 —	10 112	CLAY
		.		
3 —	30-66	3 —		
	104R5/AYLBRUN		11:	-21/
4 —	I	4 —	42-	52"/
	w/ Rocks		7.5 TR	5/6 5T-3RN,
5 —	•	5 —	CLA	Υ
	Refusal	6 _	5	2-724
6 —	1-4	0	7 7 - 7	R 5/6 5T-BRN
			1.51	KN/6 JEDIN
7 —		17 —		it-mtD-SAND
		1	72.	- 90 // (R 3 /4 Dt-YL-BRN.
8 —		8 —	\	
	.\		5/	LNDY LOAM W/GRAVEL
sad of b	poring atfeet.	End of	boring at	<u>5</u> fee:
	g water table:	1	ng water table:	
	atfeet of depth,	Presen	tatfee	er of depta.
	hours after boring,		hours aft	er boring a
	sent in boring hole		esent in boring	
Not pre	sent in boring note			•
Mottled	soil:		d soil:	
	d at feet of depth.	Observ	ed atf	eet of destr
	sent in boring hole	Not pr	esent in boring	hole
	tions and comments:		ations and comme	
			•	
	OP OF DISTRIBUTION MEDIUM AT:			INCHES
В	OTTOM OF DISTRIBUTION MEDIUM	Τ: Α. Λ. Δ. Α. Α.		INCHES
R.	EMARKS: DF SIUN 600	1 A ME) O	
W	ERE SOIL SAMPLES SPRAYED? YE	N TEL	~	

	" and the state of	Soil Bor		8-31
.ocatio:	n or Project 028	aley	ave-N'	
	made by 4 111		Date 4-	19-03
lassif	cation System: AASHO; USDA-	scs _X	_; Unified; or	her
	sed (check two): Hand \overline{X} , or Powe	r; ?:	light, or Bucket	: <u>X</u> : other
	,			·
epth,	Boring number	Depth,	Boring number	6-4
ln et	Surface elevation 998.40	in feet	Surface elevation	943,73
e (
	0-1011	0 —	6-28" 104R3/3 LOA	
	10423/2 V.DK. GR. BRD		10 4R 3/3	DK.BRN.
_	LOAMY SAND	1 -	LOA	wh synd
}		1		
-	18-36" 10 4 R 4 14 BK.YL-BASS	2 —		
	SAHOY LOAM		28-7	211
-		3 —	20	VI . 9744
	36-60"		10 YR 4/4	Dr Ir. Pkn.
-	7.44R413 BRN.	4 —	1-106	SAMD
	FINE SAND	·		
	60-96"	5 —		
	TO HIL ST-BRN			
-	7.5 YR 4/6 ST-BRN. FINE SAND	6 —	+72"	
	Plac 3/(40) +	104R 416	
		7 -	101/2 110	& MOTTLED
		1 1	16 YR 5/	
-		8 —	\ 7-5 5/	ما
Ì	.].		CLA	<u> </u>
				//
	oring at feet.	End of	boring at 65	
	water table:	Standin	g water table:	
-	at feer of depth,	Present	atfeet of	depth.
236116	hours after boring.		hours after b	
	ent in boring hole	Not pre	sent in boring hole	<u> </u>
Chres	ent in outing many		_	
ttled	soil:	Mottled	isoil: 6 feet	•
	at feet of depth.			
	sent in boring hole	Not pr	esent in boring hold	<u> </u>
	tions and comments:	Observ	ations and comments:	
			,	NCHES
	OP OF DISTRIBUTION MEDIUM AT: OTTOM OF DISTRIBUTION MEDIUM A	т.		NCHES NCHES
pr R(EMARKS: DESTRIBUTION MEDIUM A		·	
W	ERE SOIL SAMPLES SPRAYED? YES	NO NO	0	_

DISCLAIMER

Brian L. Humpal, Inc. dba. Inspect Minnesota, Midwest Soil Testing Relative to Subsurface Sewage Treatment System (SSTS) Compliance Inspections

- 1. This inspection/report is being performed for only the seller/owner of the property on which the SSTS is located. In such case that another party is paying for the inspection, the contract is between only said party and Brian L. Humpal, Inc.; there is no contract between Brian L. Humpal, Inc. and any other party unless otherwise noted.
- 3. Brian L. Humpal, Inc. has not been retained to warranty, guarantee, or certify the proper functioning of the SSTS for any period of time beyond the date of inspection or into the future. Because of the numerous factors (usage, maintenance, soil characteristics, previous failures, etc.) which may affect the proper operation of an SSTS, as well as the inability of Brian L. Humpal, Inc. to supervise or monitor the use or maintenance of the SSTS, the report shall not be construed as a warranty by Brian L. Humpal, Inc. that the SSTS will function properly for any particular party for any period of time.
- 4. Brian L. Humpal, Inc. is unable to verify the frequency and/or, quality of prior or future maintenance of the SSTS. Maintenance of the tank(s) must be performed through the tanks maintenance hole. The removal of solids from any location other than the maintenance hole is not a compliant method of maintenance. It is strongly recommended that maintenance covers be made accessible to the ground surface to facilitate proper maintenance.
- 5. Minimum Compliance Inspection requirements relative to this inspection and this report include <u>only</u> verification that the SSTS has tank(s) (septic tanks, lift tanks, dosing tanks, stilling tanks, etc.) which are watertight below the designed operating depth, the required separation between the bottom of the subsurface soil distribution medium and seasonally saturated soils, no back-ups of sewage into the dwelling, no discharge of sewage/effluent to the ground surface or surface waters, and no imminent safety hazards. Brian L. Humpal, Inc. does not inspect plumbing or pumps prior to the first SSTS component as these are plumbing components. The performance of exterior pumps and associated components are not inspected as they are considered to be maintenance items. Additionally, no indications relative to compliance with electrical code requirements have been made. It is recommended that any other applicable plumbing, electrical, housing, etc. inspections be performed by a qualified inspection business. Sewage back-up verification is limited to observing the floor drain area and/or the information supplied by the last occupants of the building prior to inspection. Brian L. Humpal, Inc. cannot guarantee that the information given to them by the last occupants of the building prior to inspection relative to back-ups is accurate.
- 4. Certification of this SSTS does not warranty future use beyond the date of the inspection. Any SSTS, old or new, can become hydraulically overloaded or discharge sewage/effluent to the ground surface as a result of more people moving into the house than were previously occupying the house, improper maintenance, heavy usage, leaking plumbing fixtures, groundwater infiltration, tree roots, freezing conditions, surface drainage problems, poor initial design, poor construction practices, or unsuitable materials used in constructing the system; the system can also simply stop working because of its age. An SSTS that has been properly designed and installed, properly maintained, and used in the manner for which the system was designed can be expected to provide service for twenty to twenty-five years on average. Some parts of the SSTS such as alarms, switches, pumps, filters, etc. will most likely have to be repaired or replaced over the lifetime of the system.
- 5. A Compliance Inspection is not meant to be a test or inspection for longevity of the system; a Compliance Inspection is strictly for the purpose of determining if the SSTS is protective of public health and safety, as well as the groundwater at the date and time the inspection was performed. This inspection is not intended to determine if the SSTS was originally designed or installed to past or present MPCA or other Local Government Unit code requirements. This inspection is not intended to determine if the SSTS was designed and/or installed to support the anticipated flow from the building as the use of the building may have changed since the design and construction of the SSTS due to the addition of bedrooms, occupants, etc. In addition, this inspection is not intended to determine the quality of the original SSTS design, the quality of the construction practices used while installing the SSTS, or the quality of the materials used in constructing the SSTS.
- 6. Brian L. Humpal, Inc. cannot guarantee the performance of SSTS products/components such as: gravelless pipe, chamber trenches, effluent filters, tanks, sewage pre-treatment components, piping, etc. Products such as gravelless pipe are no longer approved for installation in the State of Minnesota and may have a significantly reduced performance and/or life expectancy.
- 7. WINTER WORK: By accepting this report, it is understood that inspections conducted during winter months (approximately November 1st through April 1st) are more difficult to perform because of possible snow cover and/or ground frost. SSTS components such as tanks, maintenance covers, tank inspection pipes, subsurface distribution medium inspection pipes, and soil treatment areas are more difficult or impossible to locate due to snow cover and/or ground frost. In addition, soil borings are more difficult to perform due to snow cover and/or ground frost. Brian L. Humpal, Inc. will attempt to use the same level of standards when performing work during winter periods as when performing work during non-winter periods. However, the recipient of this report understands that because of the aforementioned considerations, the same level of standards may not be possible.
- 8. By accepting this report, the client understands that Brian L. Humpal, Inc. will not be responsible for any monetary damages exceeding the fee for the services provided.

Subsurface Sewage Treatment Systems

Non-transferable

Business License

Inspect Minnesota, Midwest Soil Testing

License # L2896

License Expires: 12/22/2017

Issued: 11/29/2016

Specialty Area(s):

Installer
Maintainer
Service Provider
Advanced Designer
Advanced Inspector

Designated Certified Individual(s):

Cert#

Name

Certification Expires:

C5342

Brian L Humpal

10/15/2017

Installer, Maintainer, Serv Prov, Adv Designer, Adv Inspector

C9852

Christopher R Uebe

3/4/2018

Designer, Inspector



St. Paul, Minnesota 55155-4194

Steven Giddings, Manager

Prevention and Solid Waste Management Section