

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT
GOVERNMENT CENTER
14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006
Office: 651-430-6655 TTY: 651-430-6246 FAX: 651-430-6730

Subsurface Sewage Treatment System Maintenance Permit

Roctine

This section must be completed in its entirety to constitute a valid maintenance permit. This permit must be completed prior to performing maintenance activities and remain on-site for the duration of the maintenance activity.

Tank(s) Pumped		Tank Measurement (must be completed if tanks NOT pumped)				
` ,	Tank(s) Pumped		Liquid Level of Tank in Sludge Level in Tank in Scum Level in Tank in Sludge + Scum / Liquid Level X 100 = % Sludge & Scum Tanks must be pumped if 25% or great			
Sludge and scum measured		11 -				
	Do tanks need to be pumped?					
☐ Yes ☐ No (if	no provide measurements) = % Studge & Sco	1 (A)	iks must be pumped in	25% Of great	
Were all covers so	ecurely replaced? Yes	□ No ptic. holding, pretr	eatment or pump	tank below the operat	ing depth o	
evidence of dam	of tank leakage from a se naged, cracked, or structu	rally unsound main	tenance holė cove	rs?		
	Tank	Leaking Out	Leaking In	Cover Damage		
		-				
	Septic/Holding Tank #1	☐ Yes ☑ No	☐ Yes 🗗 No	☐ Yes ☑ No		
	Septic/Holding Tank #1 Septic/Holding Tank #2	Yes No	☐ Yes ☐ No ☐ Yes ☐ No	☐ Yes ☐ No ☐ Yes ☐ No		
			_ /2	/_		

Meyer Sewer Service, Inc. 5325 Manning Ave S Afton, MN 55001 License# 915 P: 651-459-0162