

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

	System Location
ddress 11 599	ISSUORD ONE SOUTH Telephone Number Telephone Number Telephone Number Telephone Number
in HUSTING	Q5 State WPP 65033 Property ID No./GEO Code 3.1231.0001
wner! Millift A	A BSACA Pumping Date 07 27 2017
	Contractor
aintainer SCM10	WHE IS PORTCHASSA License No. 3302 Telephone Number (551.437.14)
	done to the system?
of the same of the	Tank 1: \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
] Tank(s) Pumped] Sludge and scum m	Pumped
Do tanks need to be	
Yes 🗌 No (/	If no provide measurements below/
/isual Inspection (no	ote any problems with the system); NOTE: This does not serve as a compliance inspection.
	good condition
The state of the s	*Tank Measurements-Use Only If Tank(s) Were NOT Pumped
一点影響 注意	Tank Volume (cubic inches)
Tank Length	in. X Farik Width
Tank Radius	in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.)	/ 231.01 = Liquid Capacity Gallons / Tank Depth In. = Gallons / Inch
-	in. X Gallons Per Inch = Sludge Volume Gallons
Sludge Level	Callan
Scum Level	in. X Gallons Per Inch Scurr volume
Sludge Volume	+ Scum Volume = Total Sludge and Scutti Volume
Total Sludge and Scu	rm Volume / Liquid Capacity = Percent Sludge and Scum in Tank %
Scum Layer Effluent	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.
Sludge Layer	
Signature	Wheelle Date 11.01.2017