

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## **SSTS MAINTENANCE REPORT**

· · · · · · · · · · · · · · · · · · ·	System Location	
Address 13 KIG G3KD STKEST	- PL N.	Telephone Number
City Still WatEL	Statemn ZIP CFU82	Property ID No/GEO Code
Owner Ste CWIS PETENS	Pumping Date 6.4.7	2017
100 mg 1 m	Contractor	
Maintainer SCHIOMHO PUTUS	MREALicense No. 3307	Telephone Number (\$\S\;.437.
What was done to the system?		Report Liquid Capacity in Gallons 728
Tank(s) Pumped	Tank 1;	Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3:	Pumped Tank 4: Pumped
Do tanks need to be pumped?		
Yes No (If no provide measurements belo		Pumped: 1000
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.		
*Tank Measureme	nts Use Only If Tank(s) Were	NOT Pumped
Tank Length in. <b>X</b> Tank Width in	n. <b>X</b> Tank Depth in	n. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in.	2. <b>X 3.14</b> = Tank Volume	(cubic inches)
Tank Volume (cu. in.) / <b>231.01</b> = Liquid	d Capacity Gallo	ns / Tank Depth in. = Gallons/Inch
Sludge Level in. <b>X</b> Gallons Per Inch	= Sludge Volume (	Gallons
Scum Level in. <b>X</b> Gallons Per Inch		Gallons
	•	
Sludge Volume + Scum Volume	= Total Sludge and Scum Vo	lume Gallons
Total Sludge and Scum Volume / Liquid	Capacity = Perc	ent Sludge and Scum in Tank %
		*Tanks must be pumped if either of the
	Ī_	following conditions exist:
Scum Layer	1	1. The top of the sludge layer is less than
	Tank Dooth measure	12 inches from the bottom of the outlet baffle; or
Effluent	Tank Depth measure from invert of outlet	2. Total sludge and scum volume is greater
Sludge Layer	pipe to bottom of tar	than 25 percent of the tank's liquid capacity.
Sidage Layer		
Signature / Jun / Signature	Date §-17	-17