

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006
Office: 651-430-6655 TTY: 651-430-6246 FAX: 651-430-6730

Subsurface Sewage Treatment System Maintenance Permit

Routine

This section must be completed in its entirety to constitute a valid maintenance permit. This permit must be completed prior to performing maintenance activities and remain on-site for the duration of the maintenance activity.

	nance Performed	Tank Meas	urement (must be	completed if tanks N	OT pumped)
☐ Tank(s) Pumped ☐ Sludge and scum measured ☐ Do tanks need to be pumped? ☐ Yes ☐ No (if no provide measurements)		Liquid Level of Tank in Sludge Level in Tank in Scum Level in Tank in Sludge + Scum / Liquid Level X 100 = % Sludge & Scum Tanks must be pumped if 25% or greate			
. Access used to	remove septage: Mainten	ance Hole 🗌 Other (e	enter authorization co	ode)	
	securely replaced? Yes				
evidence of da	ce of tank leakage from a se amaged, cracked, or structu	ptic, holding, preti rally unsound main	eatment or pump tenance hole cove	rs?	iting depth or
	Tank	Leaking Out	Leaking In	Cover Damage	
	Septic/Holding Tank #1	☐ Yes ☐ No	☐ Yes ☑No	☐ Yes ☐ No	
	Septic/Holding Tank #2	(□ Yes □ No	(☐ Yes ☐ No	☐ Yes ☐ No	
	Pretreatment Tank	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	
	Pump Tank	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	
	ons of septage were remove	d?			
I. How many gallo					
	<u>වට</u> gal Tank #2	gal Pretreatmen	t tankg	al Pump Tank	gal

Maintenance activities must be reported to the Department within 90 days.

Afton, MN 55001 License# 915 P: 651-459-0162