Minnesota Pollution Control Agency 520 Lafayette Road North	Compliance Inspection Form Existing Subsurface Sewage Treatment Systems (SSTS)			
St. Paul, MN 55155-4194	Doc Type: Compliance and Enforceme			
Instructions: Inspection results based on Minnesota R requirements and attached forms – additional local req				
Submit completed form to Local Unit of Governme within 15 days	nt (LUG) and system owner			
System Status				
System status on date (mm/dd/yyyy): <u>3/23</u>	2016			
Compliant – Certificate of Compli (Valid for 3 years from report date, unless s frame outlined in Local Ordinance.)	_ · ·	9		
Reason(s) for noncompliance (check all				
Impact on Public Health (Compliance Coll	nponent #1) – Imminent threat to public health and safety			

S

Other Compliance Conditions (Compliance Component #3) – Imminent threat to public health and safety

Tank Integrity (Compliance Component #2) – Failing to protect groundwater

Other Compliance Conditions (Compliance Component #3) – Failing to protect groundwater

Soil Separation (Compliance Component #4) – Failing to protect groundwater

Operating permit/monitoring plan requirements (Compliance Component #5) – Noncompliant

Property Information

Parcel ID# or Sec/Twp/Range:

Property address:	100 Red Rock Road, Newport, MN 55055	Reason for inspection: Permit
Property owner:	Ramsey/Washington Recycling Center	Owner's phone: 651-768-6678
or		
Owner's representation	ative: Ryan Tritz	Representative phone: 651-768-6678
Local regulatory au	thority: Washington County	Regulatory authority phone: 651-768-6678
Brief system descri		ng tank for scale pits. Assumed 1000 gal pre-cast holding tank
^		

Comments or recommendations:

It should be noted that the manhole covers for both tanks are buried. The scale pit manhole is approximately 58" deep and the bathroom tank manhole is approximately 7-8' deep. These manholes covers should be extended to grade to facilitate ease of access and proper maintenance of the tanks.

Certification

I hereby certify that all the necessary information has been gathered to determine the compliance status of this system. No determination of future system performance has been nor can be made due to unknown conditions during system construction, possible abuse of the system, inadequate maintenance, or future water usage.

Inspector name:	Brian Humpal	Certification number:	L5342
Business name:	Inspect Minnesota, Midwest Soil Testing	License number:	L2896
Inspector signature	e: Brian Humpal	Phone number:	651-492-7550
Necessary or □ Soil boring lo ☑ Other informa	Locally Required Attachments gs	☐ Forms per local ordinan	ce

1. Impact on Public Health – Compliance component #1 of 5

Compliance criteria:	
System discharge sewage to the ground surface.	🗌 Yes 🖾 No
System discharge sewage to drain tile or surface waters.	🗌 Yes 🛛 No
System cause sewage backup into dwelling or establishment.	🗌 Yes 🖾 No

Any "yes" answer above indicates the system is an Imminent Threat to Public Health and Safety.

Comments/Explanation:

None of the above found.

Tanks are holding tanks and pumped as needed.

Verification method(s):

- Searched for surface outlet
- Searched for seeping in yard/backup in home
- Excessive ponding in soil system/D-boxes
- Homeowner testimony (See Comments/Explanation)
- "Black soil" above soil dispersal system
- System requires "emergency" pumping
- Performed dye test
- Unable to verify (See Comments/Explanation)
- Other methods not listed (See Comments/Explanation)

2. Tank Integrity – Compliance component #2 of 5

Compliance criteria:

System consists of a seepage pit, cesspool, drywell, or leaching pit.	🗌 Yes 🛛	No
Seepage pits meeting 7080.2550 may be compliant if allowed in local ordinance.		
Sewage tank(s) leak below their designed operating depth.	🗌 Yes 🛛	No
If yes, which sewage tank(s) leaks:		

Any "yes" answer above indicates the system is Failing to Protect Groundwater.

Comments/Explanation:

Lowered underwater camera into emptied tanks - tank walls OK.

It should be noted that the manhole covers for both tanks are buried. The scale pit manhole is approximately 58" deep and the bathroom tank manhole is approximately 7-8' deep. These manholes covers should be extended to grade to facilitate ease of access and proper maintenance of the tanks.

3. Other Compliance Conditions - Compliance component #3 of 5

- a. Maintenance hole covers are damaged, cracked, unsecured, or appear to structurally unsound. 🗌 Yes* 🗌 No 🛛 Unknown
- b. Other issues (electrical hazards, etc.) to immediately and adversely impact public health or safety. \Box Yes* \boxtimes No \Box Unknown *System is an imminent threat to public health and safety

Explain:

c. System is non-protective of ground water for other conditions as determined by inspector ☐ Yes* ⊠ No *System is failing to protect groundwater

Explain:

www.pca.state.mn.us • 651-296-6300 • 800-657-3864 • TTY 651-282-5332 or 800-657-3864 • Available in alternative formats wq-wwists4-31 • 1/24/12 Page 2 of 3

Verification method(s):

- Probed tank(s) bottom
- Examined construction records
- Examined Tank Integrity Form (Attach)
- Observed liquid level below operating depth
- Examined empty (pumped) tanks(s)
- Probed outside tank(s) for "black soil"
- Unable to verify (See Comments/Explanation)
- Other methods not listed (See Comments/Explanation)

4. Soil Separation – Compliance component #4 of 5

Date of installation:	🛛 Unknown	Verification method(s):
Shoreland/Wellhead protection/Food Beverage Lodging?	🗌 Yes 🖾 N	Soil observation does not expire. Previous soil observations by two independent parties are sufficient
Compliance criteria:	1	unless site conditions have been altered or local
For systems built prior to April 1, 1996, and not located in Shoreland or Wellhead Protection Area or not serving a food, beverage or lodging establishment:	Yes IN	 requirements differ. Conducted soil observation(s) (Attach boring logs) Two previous verifications (Attach boring logs) Not applicable (Holding tank(s), no drainfield)
Drainfield has at least a two-foot vertical separation distance from periodically saturated soil or bedrock.		 Unable to verify (See Comments/Explanation) Other (See Comments/Explanation)
Non-performance systems built April 1, 1996, or later or for non-performance systems located in Shoreland or Wellhead Protection Areas or serving a food, beverage, or lodging establishment:	Yes IN	Comments/Explanation:
Drainfield has a three-foot vertical separation distance from periodically saturated soil or bedrock.*		
"Experimental", "Other", or "Performance"	🗌 Yes 🔲 N	Indicate depths of elevations
systems built under pre-2008 Rules; Type IV or V systems built under 2008 Rules (7080. 2350 or 7080.2400 (Advanced Inspector		A. Bottom of distribution media
License required)		B. Periodically saturated soil/bedrock
Drainfield meets the designed vertical separation distance from periodically		C. System separation
saturated soil or bedrock.		D. Required compliance separation*
Any "no" answer above indicates t Failing to Protect Groundwater.	he system i	*May be reduced up to 15 percent if allowed by Local Ordinance.

5. Operating Permit and Nitrogen BMP* – Compliance component #5 of 5 Not applicable

Is the system operated under an Operating Permit?	🗌 Yes 🛛 No	If "yes", A below is required
Is the system required to employ a Nitrogen BMP?	🗌 Yes 🛛 No	lf "yes", B below is required

BMP=Best Management Practice(s) specified in the system design

If the answer to both questions is "no", this section does not need to be completed.

Compliance criteria

a.	Operating Permit number: Have the Operating Permit requirements been met?	🗌 Yes 🗌 No
b.	Is the required nitrogen BMP in place and properly functioning?	Yes No

Any "no" answer indicates Noncompliance.

Upgrade Requirements (*Minn. Stat.* § 115.55) *An imminent threat to public health and safety (ITPHS) must be upgraded, replaced, or its use discontinued within ten months of receipt of this notice or within a shorter period if required by local ordinance. If the system is failing to protect ground water, the system must be upgraded, replaced, or its use discontinued within the time required by local ordinance. If an existing system is not failing as defined in law, and has at least two feet of design soil separation, then the system need not be upgraded, replaced, or its use discontinued, notwithstanding any local ordinance that is more strict. This provision does not apply to systems in shoreland areas, Wellhead Protection Areas, or those used in connection with food, beverage, and lodging establishments as defined in law.*