### **Inspect Minnesota & Midwest Soil Testing**

P.O. Box 10853 White Bear Lake, MN 55110 651-492-7550/Brian@Midwestsoiltesting.com

Brian Humpal

MPCA Licensed Advanced Inspector

#### SUBSURFACE SEWAGE TREATMENT SYSTEM (SSTS) COMPLIANCE REPORT

**Inspection Address:** 101910 110<sup>th</sup> St N, Grant, MN 55082

#### **REPORT SUMMARY**

I have performed an "MPCA Compliance Inspection" on this system, have reviewed the history of the system with the owner, Shirley Herding, and have reviewed the original design/permit records, along with previous compliance inspections from from 2006 and 2010 on file at Washington County. This very old system (installed in 1980) consists of a pre-cast septic tank, a pre-cast lift tank, and a rock trench drainfield.

Although not compliance inspection requirements, the following conditions should be noted: This house currently has six bedrooms; however, this system was permitted and installed for a three-bedroom house. The lift pump electrical connection may be prone to problems due to being inadequately protected from contact with the soil and exposure to the elements. The pump electrical connection should be re-configured to reduce the likelihood of problems. In addition, the septic tank, lift tank, and the majority of the drainfield are located beneath the deck and landscaping and are very difficult to access. Access to the tanks should be maintained during the winter months. In addition, it appears that there may be a parking area over the drainfield.

Predicated on my inspection of the system, my review of the history of the system with the owner, and my review of the previous compliance inspections, it is my opinion that this system <u>presently meets</u> MPCA minimum compliance inspection requirements.

Inspect Minnesota and Midwest Soil Testing have been hired to perform a compliance inspection of this SSTS for compliance with local ordinances pursuant to Minn. Stat. § 115.55 (2013). This compliance inspection covers only the criteria required by Minn. Stat. § 115.55 Subd. 5a (2013) and Minn. R. 7080.1500 (2011). A compliance inspection is an indication of the current compliance status of the system and does not guarantee the performance or longevity of this system beyond the date of inspection, as it is impossible to determine the future performance of any system. Inspect Minnesota and Midwest Soil Testing disclaim any use of this compliance inspection beyond determining SSTS compliance pursuant to Minn. Stat. § 115.55 Subd. 5a (2013) and Minn. R. 7080.1500 (2011).

Please contact me should you have any questions.

Brian Humpal Brian Humpal



# **Compliance Inspection Form**

# Existing Subsurface Sewage Treatment Systems (SSTS)

Doc Type: Compliance and Enforcement

<b>Instructions:</b> Inspection results based on Minnesota Pollution Control Agency (MPCA) requirements and attached forms – additional local requirements may also apply.	For local tracking purposes:
Submit completed form to Local Unit of Government (LUG) and system owner within 15 days	
System Status	
System status	
System status on date (mm/dd/yyyy): 6/18/2018	
<del></del>	npliant – Notice of Noncompliance trade Requirements on page 3)
Reason(s) for noncompliance (check all applicable)  Impact on Public Health (Compliance Component #1) – Imminent threat to Other Compliance Conditions (Compliance Component #3) – Imminent threat the Tank Integrity (Compliance Component #2) – Failing to protect groundward Other Compliance Conditions (Compliance Component #3) – Failing to protect groundward Soil Separation (Compliance Component #4) – Failing to protect groundward Operating permit/monitoring plan requirements (Compliance Component #4)	reat to public health and safety ter otect groundwater ater
Property Information Parcel ID# or Sec/Twp/Range	ge:
Property address: 10190 110 <sup>th</sup> St N, Grant, MN 55082 Reason f	or inspection: Property Transfer
Property owner: Shirley Herding Owner's	phone: 612-578-0901
or	
	ntative phone: ry authority phone: 651-430-6655
Local regulatory authority: Washington County Regulato  Brief system description: A pre-cast septic tank, a pre-cast lift tank, and a rock trend	·       ·     ·
Comments or recommendations:	on drainlieid.
Although not compliance inspection requirements, the following conditions should be n however, this system was permitted and installed for a three-bedroom house. The lift p problems due to being inadequately protected from contact with the soil and exposure connection should be re-configured to reduce the likelihood of problems. In addition, the drainfield are located beneath the deck and landscaping and are very difficult to access during the winter months. In addition, it appears that there may be a parking area over	ump electrical connection may be prone to to the elements. The pump electrical ne septic tank, lift tank, and the majority of the s. Access to the tanks should be maintained
Certification	
I hereby certify that all the necessary information has been gathered to determine the determination of future system performance has been nor can be made due to unknown possible abuse of the system, inadequate maintenance, or future water usage.	
·	ion number: L5342
	nse number: L2896
Inspector signature: Brian Humpal Pho	one number: 651-492-7550
Necessary or Locally Required Attachments	
	local ordinance
<ul> <li>✓ Other information (list): Report Summary, Property Information, Disclaimer, Lic</li> </ul>	

Prop	erty address: 10190 110th St N, Grant,	MN 55082	Inspector initials/Date: 6/18/2018				
1.	1. Impact on Public Health – Compliance component #1 of 5						
	Compliance criteria:  System discharge sewage to the ground surface.  System discharge sewage to drain tile or surface waters.  System cause sewage backup into dwelling or establishment.  Any "yes" answer above indicates an Imminent Threat to Public Heal  Comments/Explanation: None of the above found.	th and Safety.	Verification method(s):  Searched for surface outlet  Searched for seeping in yard/backup in home  Excessive ponding in soil system/D-boxes  Homeowner testimony (See Comments/Explanation)  "Black soil" above soil dispersal system  System requires "emergency" pumping  Performed dye test  Unable to verify (See Comments/Explanation)  Other methods not listed (See Comments/Explanation)				
<u>2.</u>	Tank Integrity – Compliance con	nponent #2 of 5					
	Compliance criteria:  System consists of a seepage pit, cesspool, drywell, or leaching pit.  Seepage pits meeting 7080.2550 may be compliant if allowed in local ordinance.	☐ Yes ☒ No	Verification method(s):  ☑ Probed tank(s) bottom ☑ Examined construction records ☐ Examined Tank Integrity Form (Attach) ☐ Observed liquid level below operating depth				
	Sewage tank(s) leak below their designed operating depth.  If yes, which sewage tank(s) leaks:  Any "yes" answer above indicates system is Failing to Protect Green.		<ul> <li>□ Examined empty (pumped) tanks(s)</li> <li>□ Probed outside tank(s) for "black soil"</li> <li>□ Unable to verify (See Comments/Explanation)</li> <li>□ Other methods not listed (See Comments/Explanation)</li> </ul>				
3.	Comments/Explanation: Lowered underwater camera into tanks - Lift pump and alarm were operational at  Other Compliance Conditions	the time of the inspection.	nt #3 of 5				
	<ul> <li>a. Maintenance hole covers are damaged, cracked, unsecured, or appear to structurally unsound. ☐ Yes* ☐ No ☐ Unknown</li> <li>b. Other issues (electrical hazards, etc.) to immediately and adversely impact public health or safety. ☐ Yes* ☐ No ☐ Unknown *System is an imminent threat to public health and safety</li> <li>Explain:</li> <li>c. System is non-protective of ground water for other conditions as determined by inspector ☐ Yes* ☐ No *System is failing to protect groundwater</li> <li>Explain:</li> </ul>						

www.pca.state.mn.us • 651-296-6300 • 800-657-3864 • TTY 651-282-5332 or 800-657-3864 • Available in alternative formats wq-wwists4-31 • 1/24/12 Page 2 of 3

Property address: 10190 110th St N, Grant, MN 55082

Inspector initials/Date: 6/18/2018

4.	Soil Separation – Compliance compor	nent #4 of 5				
	Date of installation: 1980	Unknown	V	erification method(s):		
	Shoreland/Wellhead protection/Food Beverage Lodging?	☐ Yes ⊠ No	s	oil observation does not expire. Pr		
	Compliance criteria:		u	bservations by two independent pa nless site conditions have been alt		
	For systems built prior to April 1, 1996, and not located in Shoreland or Wellhead Protection Area or not serving a food, beverage or lodging establishment:  Drainfield has at least a two-foot vertical	⊠ Yes □ No	_	equirements differ.  Conducted soil observation(s) (A  Two previous verifications (Attac  Not applicable (Holding tank(s), no  Unable to verify (See Comments/b)	ch boring logs) o drainfield)	
	separation distance from periodically saturated soil or bedrock.			Other (See Comments/Explanation)		
	Non-performance systems built April 1,	☐ Yes ☐ No	C	comments/Explanation:		
	1996, or later or for non-performance systems located in Shoreland or Wellhead		R	eviewed previous compliance insp	ection from 2010.	
	Protection Areas or serving a food, beverage, or lodging establishment:		R	eviewed previous compliance insp	ection from 2006.	
	Drainfield has a three-foot vertical separation distance from periodically saturated soil or bedrock.*		R	eviewed design and permit record	S.	
	"Experimental", "Other", or "Performance"	☐ Yes ☐ No	_ <u>  Ir</u>	ndicate depths of elevations		
	systems built under pre-2008 Rules; Type IV or V systems built under 2008 Rules (7080. 2350 or 7080.2400 (Advanced Inspector License required)		_A.	Bottom of distribution media	See Attached Boring Log(s)	
	Drainfield meets the designed vertical		_B.	Periodically saturated soil/bedrock		
	separation distance from periodically saturated soil or bedrock.		<u>C</u> .	System separation		
			D.	Required compliance separation*		
			May be reduced up to 15 percent if Ordinance.	allowed by Local		
5.	Operating Permit and Nitrogen B	MP* – Compliand	ce com	ponent #5 of 5 Not appl	icable	
	Is the system operated under an Operating Per		⊠ No	If "yes", A below is required		
	Is the system required to employ a Nitrogen BM			If "yes", B below is required		
	BMP=Best Management Practice(s) specified in the system design					
	If the answer to both questions is "no",	this section doe	s not ı	need to be completed.		
	Compliance criteria					
	a. Operating Permit number:			□ Vee □ Ne		
	Have the Operating Permit requirements I	peen met?		☐ Yes ☐ No		
	b. Is the required nitrogen BMP in place and	properly functioning	g?	☐ Yes ☐ No		
	Any "no" answer indicates Noncompliance.					

Upgrade Requirements (Minn. Stat. § 115.55) An imminent threat to public health and safety (ITPHS) must be upgraded, replaced, or its use discontinued within ten months of receipt of this notice or within a shorter period if required by local ordinance. If the system is failing to protect ground water, the system must be upgraded, replaced, or its use discontinued within the time required by local ordinance. If an existing system is not failing as defined in law, and has at least two feet of design soil separation, then the system need not be upgraded, repaired, replaced, or its use discontinued, notwithstanding any local ordinance that is more strict. This provision does not apply to systems in shoreland areas, Wellhead Protection Areas, or those used in connection with food, beverage, and lodging establishments as defined in law.

www.pca.state.mn.us • 651-296-6300 • 800-657-3864 TTY 651-282-5332 or 800-657-3864 • Available in alternative formats wq-wwists4-31 • 1/24/12 Page 3 of 3

# Inspect Minnesota & Midwest Soil Testing Subsurface Sewage Treatment System Owner/Property Information

This information will be used for the purpose of conducting an MPCA Compliance Inspection.

Date of Inspection: June 18, 2018	Time: 8:45 AM		
Property Address: 10190 110 <sup>th</sup> St N, Grant, MN	Zip: 55082		
Property Owner: Shirley Herding	Phone: 612-578-0901		
Tank(s)       Tank(s)Material       Soil Treatment System            □ Septic 1       □ Fiberglass       □ Rock trench         □ Aerobic       □ Plastic       □ Gravelless trench         □ Lift       □ Metal       □ Chamber trench         □ Holding       □ Concrete       □ Seepage bed         □ Other:       □ Block       □ Mound         □ Other       □ At-grade	Other  Alternative system  Experimental system  Cesspool system  Other system		
Are the tank maintenance covers accessible?   Yes   No *If r performed through the maintenance holes. Maintenance hole cover the ground surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface to facilitate access and proper maintenance of the second surface access and proper maintenance of the second surface access and second surface access access and second surface access ac	ers should be made accessible to		
1	Tank size (gals.): 1200		
How long has seller owned the property? 2011 Number of res	sidents in home? 2		
Number of bedrooms? 6 Are all floors drained by gr	ravity? Y		
Garbage disposal? N Whirlpool bath?	N		
More than one system (laundry, etc.)? N			
Does this property have any footing drain tiles connected to the septic system? N  Are any buildings on this property such as garages or out-buildings connected to this system? N			
Are there any additional systems on this property serving other buildings? N			
Location of septic system on lot? South Side			
	well a deep well? Y		
Have you ever experienced any problems with the system such as: tree roots, sewage back-ups, surfacing of sewage onto the ground, septic tank overflowing, etc.; or have any repairs been made to the system? N If yes, explain:			
When was the system last pumped? June 2018 Name of pumper: Pinky's Sewer Service			
How often pumped in previous years? Every 3  Is system on a monitoring plan? N			
Have you received notices from any government agency concerning this system? N			
Is your property located in a shoreland management area? N			
Do you have any additional information that should be given to the new owner? N			

I hereby certify that the above information is correct to the best of my knowledge. I also understand that if the system is considered "non-compliant/failing" per MPCA rules, that the inspector must by law submit a copy of this report to the local government unit within 15 days of the date of inspection completion. I also agree that unless otherwise noted in this report, that I/we are ultimately responsible for payment of all fees for all work performed relative to this inspection by Inspect Minnesota and Midwest Soil Testing.

Owner/Occupant: Shirley Herding's Signature On File Date: 06/18/2018

## **Log Of Soil Borings**

Location of Project: 10190 110th Street, Grant, MN 55082					
Borings Made By: Inspect Minnesota		Date:		12/30/10	
Auger Used: Hand/Bucket		Classification System:		USDA	
	Boring Number:	1		Boring Number:	
Surface	10" Downslop	oe of ground surface	Surface		
Elevation	of at end of "L	" shaped drainfield	Elevation (	of	
Boring		trench	Boring		
Depth In	Soils E	ncountered	Depth In	Soils Er	ncountered
Inches 0-18		am With Trace Gravel	Inches		
18-54 54-64	7.5YR 5/6 Silty Cla 7.5YR 4/6 S	y Loam W/Trace Gravel Sandy Clay Loam oam With Trace Gravels			
06"	Double To Find Of D	aving On Matthed Caile		Doubh To Fred Of D	oving On Matthed Caile
		oring Or Mottled Soils			oring Or Mottled Soils
		g Relative To System			Relative To System
72" Depth To Bottom Of System			Depth To Bottom C	of System	
≥34"	Of Separation			Of Separation	
	End Of Boring At:	96"		End Of Boring At:	
	ed Soil Present At:	None	Mottle	ed Soil Present At:	
	Water Present At:	None	Standing	Water Present At:	

<b>Bottom</b>	Of I	Distribution	Medium At:	72	Inches
DOLLOIII	OI L	715ti 10utioi i	Mediuili At.	//	mones

	ander by <u>Inspect</u> MN estion System: AASHO; USDA ed (check two): Hand <u>X</u> , or Pow		; Unified	
—-г		·		
h,	Boring number	Depth,	Boring num	
	surface elevation Same 45 top of ground @ end of L" Shaped trench	feet	Surface el	evation
	"-12" TOPSOIL	0 -		
			•	
	"-20" 7.5 YR 5/4 Sandy.	.   1 —	•	
}	1,24. mm	.   ,		. · · · · · · · · · · · · · · · · · · ·
ľ	10"-40" 7.54R 4/4 Clay		•	• •
-		3 —	•	
4	10"-96" 7.5 YR 41/6.			•
-	10"-96" 7.5 YR 41/6 Sandy Isam YTrace gravel + Rocks	4 —		
ļ	YTrace curavel + Rocks			
-		5 —		
		6 _ ]		
			•	
.	·	7 —		
.  -		8 —		
	: • · · · · · · · • · · · · · · · · · ·			
of Bor	ing at: 96 Inches	End of I	Boring at:	_ Inches
led Soled So	il Present: Yes NO il at: Inches		Soil Present: Y Soil at:	•
ling V	Vater Present: Yes NO Vater Present at: Inches		g Water Present g Water Present	

When performing the soil boring (s) relative to this septic system inspection, site evaluation or design, the depth to distinct redoximorphic features (commonly know as "mottled soils") were determined by using the definition for "distinct" as defined in MPCA rules 7080.0020 Subp. 13a. adopted through September 2002: "Distinct" means a soil color that varies from another color by one or more hues, more than two units of value, or more than one unit of chroma.

(A:I has been advised through training and conversations with the MPCA that the above procedure for determining redoximorphic features (mottled soils) must be used in all cases; no other definitions will be allowed. The only exceptions would be when the difference in soil colors are attributed to other soil features such as lamellae banding, chelation from tannic acids, calcium carbonates, etc.

#### **DISCLAIMER**

# Brian L. Humpal, Inc. dba. Inspect Minnesota, Midwest Soil Testing Relative to Subsurface Sewage Treatment System (SSTS) Compliance Inspections

- 1. This inspection/report is being performed for only the seller/owner of the property on which the SSTS is located. In such case that another party is paying for the inspection, the contract is between only said party and Brian L. Humpal, Inc.; there is no contract between Brian L. Humpal, Inc. and any other party unless otherwise noted.
- 3. Brian L. Humpal, Inc. has not been retained to warranty, guarantee, or certify the proper functioning of the SSTS for any period of time beyond the date of inspection or into the future. Because of the numerous factors (usage, maintenance, soil characteristics, previous failures, etc.) which may affect the proper operation of an SSTS, as well as the inability of Brian L. Humpal, Inc. to supervise or monitor the use or maintenance of the SSTS, the report shall not be construed as a warranty by Brian L. Humpal, Inc. that the SSTS will function properly for any particular party for any period of time.
- 4. Brian L. Humpal, Inc. is unable to verify the frequency and/or, quality of prior or future maintenance of the SSTS. Maintenance of the tank(s) must be performed through the tanks maintenance hole. The removal of solids from any location other than the maintenance hole is not a compliant method of maintenance. It is strongly recommended that maintenance covers be made accessible to the ground surface to facilitate proper maintenance.
- 5. Minimum Compliance Inspection requirements relative to this inspection and this report include <u>only</u> verification that the SSTS has tank(s) (septic tanks, lift tanks, dosing tanks, stilling tanks, etc.) which are watertight below the designed operating depth, the required separation between the bottom of the subsurface soil distribution medium and seasonally saturated soils, no back-ups of sewage into the dwelling, no discharge of sewage/effluent to the ground surface or surface waters, and no imminent safety hazards. Brian L. Humpal, Inc. does not inspect plumbing or pumps prior to the first SSTS component as these are plumbing components. The performance of exterior pumps and associated components are not inspected as they are considered to be maintenance items. Additionally, no indications relative to compliance with electrical code requirements have been made. It is recommended that any other applicable plumbing, electrical, housing, etc. inspections be performed by a qualified inspection business. Sewage back-up verification is limited to observing the floor drain area and/or the information supplied by the last occupants of the building prior to inspection. Brian L. Humpal, Inc. cannot guarantee that the information given to them by the last occupants of the building prior to inspection relative to back-ups is accurate.
- 4. Certification of this SSTS does not warranty future use beyond the date of the inspection. Any SSTS, old or new, can become hydraulically overloaded or discharge sewage/effluent to the ground surface as a result of more people moving into the house than were previously occupying the house, improper maintenance, heavy usage, leaking plumbing fixtures, groundwater infiltration, tree roots, freezing conditions, surface drainage problems, poor initial design, poor construction practices, or unsuitable materials used in constructing the system; the system can also simply stop working because of its age. An SSTS that has been properly designed and installed, properly maintained, and used in the manner for which the system was designed can be expected to provide service for twenty to twenty-five years on average. Some parts of the SSTS such as alarms, switches, pumps, filters, etc. will most likely have to be repaired or replaced over the lifetime of the system.
- 5. A Compliance Inspection is not meant to be a test or inspection for longevity of the system; a Compliance Inspection is strictly for the purpose of determining if the SSTS is protective of public health and safety, as well as the groundwater at the date and time the inspection was performed. This inspection is not intended to determine if the SSTS was originally designed or installed to past or present MPCA or other Local Government Unit code requirements. This inspection is not intended to determine if the SSTS was designed and/or installed to support the anticipated flow from the building as the use of the building may have changed since the design and construction of the SSTS due to the addition of bedrooms, occupants, etc. In addition, this inspection is not intended to determine the quality of the original SSTS design, the quality of the construction practices used while installing the SSTS, or the quality of the materials used in constructing the SSTS.
- 6. Brian L. Humpal, Inc. cannot guarantee the performance of SSTS products/components such as: gravelless pipe, chamber trenches, effluent filters, tanks, sewage pre-treatment components, piping, etc. Products such as gravelless pipe are no longer approved for installation in the State of Minnesota and may have a significantly reduced performance and/or life expectancy.
- 7. WINTER WORK: By accepting this report, it is understood that inspections conducted during winter months (approximately November 1<sup>st</sup> through April 1<sup>st</sup>) are more difficult to perform because of possible snow cover and/or ground frost. SSTS components such as tanks, maintenance covers, tank inspection pipes, subsurface distribution medium inspection pipes, and soil treatment areas are more difficult or impossible to locate due to snow cover and/or ground frost. In addition, soil borings are more difficult to perform due to snow cover and/or ground frost. Brian L. Humpal, Inc. will attempt to use the same level of standards when performing work during winter periods as when performing work during non-winter periods. However, the recipient of this report understands that because of the aforementioned considerations, the same level of standards may not be possible.
- 8. By accepting this report, the client understands that Brian L. Humpal, Inc. will not be responsible for any monetary damages exceeding the fee for the services provided.

# Subsurface Sewage Treatment Systems Non-transferable Business License

# Inspect Minnesota, Midwest Soil Testing

License # L2896

License Expires: 12/22/2018

Issued: 10/10/2017

es:

# Specialty Area(s):

Installer
Maintainer
Service Provider
Advanced Designer
Advanced Inspector

# Designated Certified Individual(s):

Cert #	Name	Certification Expir
C9633	Anthony P Scully	7/28/2018
	Installer, Designer (Conditional)	
C5342	Brian L Humpal	10/15/2020
	Installer, Maintainer, Serv Prov,	Adv Designer, Adv Inspector
C9852	Christopher R Uebe	3/4/2018
	Designer, Inspector	



520 Lafayette Road North St. Paul, Minnesota 55155-4194 Charles & Thompson

Charles K Thompson, Supervisor Certification & Training Unit