Inspect Minnesota & Midwest Soil Testing

P.O. Box 10853 White Bear Lake, MN 55110 651-492-7550/Brian@Midwestsoiltesting.com

Brian Humpal

MPCA Licensed Advanced Inspector

SUBSURFACE SEWAGE TREATMENT SYSTEM (SSTS) COMPLIANCE REPORT

Inspection Address: 812 Julep Ave N, Lake Elmo, MN 55042

REPORT SUMMARY

I have performed an "MPCA Compliance Inspection" on this system, have reviewed the history of the system with the owner, Todd Ptacek, and have reviewed the original design/permit records on file at the City of Lake Elmo. This system consists of two pre-cast septic tanks, a precast lift tank, and a mound.

Predicated on my inspection of the system, my review of the history of the system with the owner, and my review of the original design/permit records, it is my opinion that this system presently meets MPCA minimum compliance inspection requirements.

Inspect Minnesota and Midwest Soil Testing have been hired to perform a compliance inspection of this SSTS for compliance with local ordinances pursuant to Minn. Stat. § 115.55 (2013). This compliance inspection covers only the criteria required by Minn. Stat. § 115.55 Subd. 5a (2013) and Minn. R. 7080.1500 (2011). A compliance inspection is an indication of the current compliance status of the system and does not guarantee the performance or longevity of this system beyond the date of inspection, as it is impossible to determine the future performance of any system. Inspect Minnesota and Midwest Soil Testing disclaim any use of this compliance inspection beyond determining SSTS compliance pursuant to Minn. Stat. § 115.55 Subd. 5a (2013) and Minn. R. 7080.1500 (2011).

Please contact me should you have any questions.

Christopher Uebe

Brian Humpal

Brian Humpal



Compliance Inspection Form

Existing Subsurface Sewage Treatment Systems (SSTS)

Doc Type: Compliance and Enforcement

Instructions: Inspection results based on Minnesota Pollution Control Agency (MPCA) requirements and attached forms – additional local requirements may also apply.	For local tracking purposes:
Submit completed form to Local Unit of Government (LUG) and system owner within 15 days	
System Status	
System status on date (mm/dd/yyyy):	
_ ·	mpliant – Notice of Noncompliance grade Requirements on page 3)
Reason(s) for noncompliance (check all applicable) ☐ Impact on Public Health (Compliance Component #1) – Imminent threat to ☐ Other Compliance Conditions (Compliance Component #3) – Imminent thi ☐ Tank Integrity (Compliance Component #2) – Failing to protect groundwa ☐ Other Compliance Conditions (Compliance Component #3) – Failing to protect groundwa ☐ Soil Separation (Compliance Component #4) – Failing to protect groundwa ☐ Operating permit/monitoring plan requirements (Compliance Component #4)	reat to public health and safety ter otect groundwater vater
Property Information Parcel ID# or Sec/Twp/Range	ge:
•	for inspection: Property Transfer
Property owner: Todd Ptacek Owner's	phone:
or	
•	ntative phone: 651 430 6655
Local regulatory authority: Washington County Regulato Brief system description: Two pre-cast septic tanks, a pre-cast lift tank, and a mount	ry authority phone: <u>651-430-6655</u>
Comments or recommendations:	iu.
Comments of recommendations.	
Certification	
I hereby certify that all the necessary information has been gathered to determine the determination of future system performance has been nor can be made due to unknown possible abuse of the system, inadequate maintenance, or future water usage.	
	ion number: C5342/C9852
· ·	nse number: L2896
Brian Humpal Ut- 11.	one number: 651-492-7550
Necessary or Locally Required Attachments	
	local ordinance
☐ Other information (list): Report Summary, Property Information, Disclaimer, Lice	

Property address: 812 Julep Ave N, Lake Elmo, MN 55042

Inspector initials/Date: 7/9/2018 4 ()

1.	ln	npact on Public Health – Con	npliance compo	ent #1 of 5
	Sy gro Sy or Sy dw An	extem discharge sewage to the bound surface. Extem discharge sewage to drain tile surface waters. Extem cause sewage backup into extem cause sewage backup into extension of the surface waters. Extem cause sewage backup into extension of the above found.		Verification method(s): Searched for surface outlet Searched for seeping in yard/backup in home Excessive ponding in soil system/D-boxes Homeowner testimony (See Comments/Explanation) "Black soil" above soil dispersal system System requires "emergency" pumping Performed dye test Unable to verify (See Comments/Explanation) Other methods not listed (See Comments/Explanation)
2.		ank Integrity — Compliance com	ponent #2 of 5	Verification method(s):
2	Syce Secon Secon Manual Sy Coc Loc Liff	restem consists of a seepage pit, sspool, drywell, or leaching pit. Repage pits meeting 7080.2550 may be impliant if allowed in local ordinance. Rewage tank(s) leak below their issigned operating depth. Reyes, which sewage tank(s) leaks: Reye	baffles and tank	 □ Probed tank(s) bottom □ Examined construction records □ Examined Tank Integrity Form (Attach) □ Observed liquid level below operating depth □ Examined empty (pumped) tanks(s) □ Probed outside tank(s) for "black soil" □ Unable to verify (See Comments/Explanation) □ Other methods not listed (See Comments/Explanation)
3.	A. Maintenance hole covers are damaged, cracked, unsecured, or appear to structurally unsound. ☐ Yes* ☑ No ☐ Unknown b. Other issues (electrical hazards, etc.) to immediately and adversely impact public health or safety. ☐ Yes* ☑ No ☐ Unknown *System is an imminent threat to public health and safety Explain: c. System is non-protective of ground water for other conditions as determined by inspector ☐ Yes* ☑ No *System is failing to protect groundwater Explain:			

www.pca.state.mn.us • 651-296-6300 • 800-657-3864 • TTY 651-282-5332 or 800-657-3864 • Available in alternative formats wq-wwists4-31 • 1/24/12 Page 2 of 3

Property address: _812 Julep Ave N, Lake Elmo, MN 55042				Inspector initials/Date:	7/9/2018 BH ()	
4.						
	Date of installation: 1998 Shoreland/Wellhead protection/Food Beverage Lodging? Compliance criteria:	☐ Yes ☒ No Si ob un		Verification method(s): Soil observation does not expire. Previous soil observations by two independent parties are sufficient unless site conditions have been altered or local		
	For systems built prior to April 1, 1996, and not located in Shoreland or Wellhead Protection Area or not serving a food, beverage or lodging establishment: Drainfield has at least a two-foot vertical separation distance from periodically saturated soil or bedrock.	☐ Yes ☐	No	Unable to verify (See Commo	Attach boring logs) s), no drainfield) ents/Explanation)	
	Non-performance systems built April 1, 1996, or later or for non-performance systems located in Shoreland or Wellhead Protection Areas or serving a food, beverage, or lodging establishment: Drainfield has a three-foot vertical separation distance from periodically saturated soil or bedrock.*	⊠ Yes □		omments/Explanation: eviewed design and permit re	cords.	
	"Experimental", "Other", or "Performance" systems built under pre-2008 Rules; Type IV or V systems built under 2008 Rules (7080. 2350 or 7080.2400 (Advanced Inspector License required) Drainfield meets the designed vertical separation distance from periodically saturated soil or bedrock.	☐ Yes ☐	<u>А.</u> В.	Bottom of distribution media Periodically saturated soil/bedro	See Attached Boring Log(s)	
5.	Any "no" answer above indicates the system is Failing to Protect Groundwater. Operating Permit and Nitrogen BMP* – Compliance		*M	Required compliance separation May be reduced up to 15 perce Ordinance.		
Is the system operated under an Operating Permit?						
	Operating Permit number: Have the Operating Permit requirements been met?			☐ Yes ☐ No		
	b. Is the required nitrogen BMP in place and properly functioning?					

Any "no" answer indicates Noncompliance.

Upgrade Requirements (Minn. Stat. § 115.55) An imminent threat to public health and safety (ITPHS) must be upgraded, replaced, or its use discontinued within ten months of receipt of this notice or within a shorter period if required by local ordinance. If the system is failing to protect ground water, the system must be upgraded, replaced, or its use discontinued within the time required by local ordinance. If an existing system is not failing as defined in law, and has at least two feet of design soil separation, then the system need not be upgraded, repaired, replaced, or its use discontinued, notwithstanding any local ordinance that is more strict. This provision does not apply to systems in shoreland areas, Wellhead Protection Areas, or those used in connection with food, beverage, and lodging establishments as defined in law.

www.pca.state.mn.us • 651-296-6300 • 800-657-3864 TTY 651-282-5332 or 800-657-3864 • Available in alternative formats wq-wwists4-31 • 1/24/12 Page 3 of 3


Inspect Minnesota & Midwest Soil Testing Subsurface Sewage Treatment System Owner/Property Information

This information will be used for the purpose of conducting an MPCA Compliance Inspection.

Date of Inspection: July 9, 2018	Time: 2:00 PM		
Property Address: 812 Julep Ave N, Lake Elmo, MN Zip: 55042			
Property Owner: Todd Ptacek	Phone:		
Tank(s) Tank(s)Material Soil Treatment System	Other		
Septic 2	Alternative system Experimental system Cesspool system Other system		
Are the tank maintenance covers accessible? ⊠ Yes □ No *If performed through the maintenance holes. Maintenance hole cover the ground surface to facilitate access and proper maintenance of	ers should be made accessible to		
Year house built: 1998 Year septic installed: 1998	Tank size (gals.): 2-1000		
How long has seller owned the property? 1998 Number of re	esidents in home? 2-4		
Number of bedrooms? 4 Are all floors drained by §	gravity? N		
Garbage disposal? N Whirlpool bath	? Y		
More than one system (laundry, etc.)? N			
Does this property have any footing drain tiles connected to the septic system? N Are any buildings on this property such as garages or out-buildings connected to this system? N			
Are there any additional systems on this property serving other buildings? N			
Location of septic system on lot? North Side			
Location of water well on lot? South Side	e well a deep well? Y		
Have you ever experienced any problems with the system such as: tree roots, sewage back-ups,			
surfacing of sewage onto the ground, septic tank overflowing, etc.; or have any repairs been made to the system? N If yes, explain:			
When was the system last pumped? 2017 Name of pumper: Pinky's Sewer Service			
How often pumped in previous years? Every 2			
Have you received notices from any government agency concerning this system? N			
Is your property located in a shoreland management area? N			
Do you have any additional information that should be given to the new owner? N			

I hereby certify that the above information is correct to the best of my knowledge. I also understand that if the system is considered "non-compliant/failing" per MPCA rules, that the inspector must by law submit a copy of this report to the local government unit within 15 days of the date of inspection completion. I also agree that unless otherwise noted in this report, that I/we are ultimately responsible for payment of all fees for all work performed relative to this inspection by Inspect Minnesota and Midwest Soil Testing.

Owner/Occupant: Todd Ptacek's Signature On File Date: 7/9/2018



Log Of Soil Borings

Location of Project: 812 Julep Ave N, Lake Elmo, MN 55042						
Borings Made By: Inspect Minnesota		Date: 7/9/		7/9/18		
Auger Used: Hand/Bucket		Classification System: USDA		USDA		
	Boring Number: 1			Boring Number:		
Surface Elevation Boring	of 75" Below	top of mound on nal contour	Surface Elevation of Boring	of		
Depth In Inches	Soils E	ncountered	Depth In Inches	Soils Er	countered	
0-18 18-24	7.5YR 5/8 & 10YR 3/4 S	andy Loam With 10YR 6/2 Redox andy Loam With 10YR 6/2 Redox				
0"	Depth To End Of B	oring Or Redox]	Depth To End Of Bo	oring Or Redox	
+75"					Relative To System	
	Elevation Of Boring Below Top Of Mound				•	
-33" Depth To Bottom Of Distribution Media =42" Of Separation			Of Separation	of Distribution Media		
-72 (OI Separation				<u> </u>		
End Of Boring At: 24"		24"		End Of Boring At:		
Redox Present At: 0"			Redox Present At:			
Standing Water Present At: None		Standing	Water Present At:			

Bottom Of Distribution Medium At: 33 Inches	

SITE 1

PERCOLATION TEST FAILED

DATE 5-13-98

BOREHOLE DIAMETER 4"-3% FOUR RUSCP

		(8 of 10			818
HOLE #6	MIXTURE - LOPNY AND BLACK DIRT -	5012 15 UERY	4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		 	
HOLE #5	TOP SOIL BROWN LOAM WITH SAND LAYERS	BROWN, SAIDBY -		BROWN LOAN) WITH SAND LANERS STOP	MOTILE S'	
HOLE #4	- RROWN LOAM WITH SAND	Brown, Shuby	+++++	MOTHED SOIL	Monue 5'	
HOLE #3	BLACK DIRT BROWN LOANS WITH SAND LAYERS	BROWN, SANDY LOAM	Monzed Soll- BROWN LOAM	72/5	Monte 4	
HOLE #2	619CK DIRT	STRONG BROWN, SANDY LORIN	FRINT MOTTE MOTED SOIL - BROWN LOAM WITH SAND LAYERS	\$0.50 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	-+ Worte +-	
HOLE #1	BLACK DIRT.	- BROWN 10AM	ElGHT BON- BROWN, SANDY LOAM- LIGHT NOTTLE		More 4'	
DEPTH		7 m	4 rv		L 8	9 110

DISCLAIMER

Brian L. Humpal, Inc. dba. Inspect Minnesota, Midwest Soil Testing Relative to Subsurface Sewage Treatment System (SSTS) Compliance Inspections

- 1. This inspection/report is being performed for only the seller/owner of the property on which the SSTS is located. In such case that another party is paying for the inspection, the contract is between only said party and Brian L. Humpal, Inc.; there is no contract between Brian L. Humpal, Inc. and any other party unless otherwise noted.
- 3. Brian L. Humpal, Inc. has not been retained to warranty, guarantee, or certify the proper functioning of the SSTS for any period of time beyond the date of inspection or into the future. Because of the numerous factors (usage, maintenance, soil characteristics, previous failures, etc.) which may affect the proper operation of an SSTS, as well as the inability of Brian L. Humpal, Inc. to supervise or monitor the use or maintenance of the SSTS, the report shall not be construed as a warranty by Brian L. Humpal, Inc. that the SSTS will function properly for any particular party for any period of time.
- 4. Brian L. Humpal, Inc. is unable to verify the frequency and/or, quality of prior or future maintenance of the SSTS. Maintenance of the tank(s) must be performed through the tanks maintenance hole. The removal of solids from any location other than the maintenance hole is not a compliant method of maintenance. It is strongly recommended that maintenance covers be made accessible to the ground surface to facilitate proper maintenance.
- 5. Minimum Compliance Inspection requirements relative to this inspection and this report include <u>only</u> verification that the SSTS has tank(s) (septic tanks, lift tanks, dosing tanks, stilling tanks, etc.) which are watertight below the designed operating depth, the required separation between the bottom of the subsurface soil distribution medium and seasonally saturated soils, no back-ups of sewage into the dwelling, no discharge of sewage/effluent to the ground surface or surface waters, and no imminent safety hazards. Brian L. Humpal, Inc. does not inspect plumbing or pumps prior to the first SSTS component as these are plumbing components. The performance of exterior pumps and associated components are not inspected as they are considered to be maintenance items. Additionally, no indications relative to compliance with electrical code requirements have been made. It is recommended that any other applicable plumbing, electrical, housing, etc. inspections be performed by a qualified inspection business. Sewage back-up verification is limited to observing the floor drain area and/or the information supplied by the last occupants of the building prior to inspection. Brian L. Humpal, Inc. cannot guarantee that the information given to them by the last occupants of the building prior to inspection relative to back-ups is accurate.
- 4. Certification of this SSTS does not warranty future use beyond the date of the inspection. Any SSTS, old or new, can become hydraulically overloaded or discharge sewage/effluent to the ground surface as a result of more people moving into the house than were previously occupying the house, improper maintenance, heavy usage, leaking plumbing fixtures, groundwater infiltration, tree roots, freezing conditions, surface drainage problems, poor initial design, poor construction practices, or unsuitable materials used in constructing the system; the system can also simply stop working because of its age. An SSTS that has been properly designed and installed, properly maintained, and used in the manner for which the system was designed can be expected to provide service for twenty to twenty-five years on average. Some parts of the SSTS such as alarms, switches, pumps, filters, etc. will most likely have to be repaired or replaced over the lifetime of the system.
- 5. A Compliance Inspection is not meant to be a test or inspection for longevity of the system; a Compliance Inspection is strictly for the purpose of determining if the SSTS is protective of public health and safety, as well as the groundwater at the date and time the inspection was performed. This inspection is not intended to determine if the SSTS was originally designed or installed to past or present MPCA or other Local Government Unit code requirements. This inspection is not intended to determine if the SSTS was designed and/or installed to support the anticipated flow from the building as the use of the building may have changed since the design and construction of the SSTS due to the addition of bedrooms, occupants, etc. In addition, this inspection is not intended to determine the quality of the original SSTS design, the quality of the construction practices used while installing the SSTS, or the quality of the materials used in constructing the SSTS.
- 6. Brian L. Humpal, Inc. cannot guarantee the performance of SSTS products/components such as: gravelless pipe, chamber trenches, effluent filters, tanks, sewage pre-treatment components, piping, etc. Products such as gravelless pipe are no longer approved for installation in the State of Minnesota and may have a significantly reduced performance and/or life expectancy.
- 7. WINTER WORK: By accepting this report, it is understood that inspections conducted during winter months (approximately November 1st through April 1st) are more difficult to perform because of possible snow cover and/or ground frost. SSTS components such as tanks, maintenance covers, tank inspection pipes, subsurface distribution medium inspection pipes, and soil treatment areas are more difficult or impossible to locate due to snow cover and/or ground frost. In addition, soil borings are more difficult to perform due to snow cover and/or ground frost. Brian L. Humpal, Inc. will attempt to use the same level of standards when performing work during winter periods as when performing work during non-winter periods. However, the recipient of this report understands that because of the aforementioned considerations, the same level of standards may not be possible.
- 8. By accepting this report, the client understands that Brian L. Humpal, Inc. will not be responsible for any monetary damages exceeding the fee for the services provided.

Subsurface Sewage Treatment Systems Non-transferable Business License

Inspect Minnesota, Midwest Soil Testing

License # L2896

License Expires: 12/22/2018

Issued: 10/10/2017

es:

Specialty Area(s):

Installer
Maintainer
Service Provider
Advanced Designer
Advanced Inspector

Designated Certified Individual(s):

Cert #	Name	Certification Expir
C9633	Anthony P Scully	7/28/2018
	Installer, Designer (Conditional)	
C5342	Brian L Humpal	10/15/2020
	Installer, Maintainer, Serv Prov,	Adv Designer, Adv Inspector
C9852	Christopher R Uebe	3/4/2018
	Designer, Inspector	



520 Lafayette Road North St. Paul, Minnesota 55155-4194 Charles & Thompson

Charles K Thompson, Supervisor Certification & Training Unit