Minnesota Pollution Control Agency
520 Lafayette Road North
St. Paul, MN 55155-4194

Compliance Inspection Form

Existing Subsurface Sewage Treatment Systems

(SSTS)

Doc Type: Compliance and Enforcement

nstructions: Inspection results based on Minnesota Pollution Control Agency (MPCA) requirements and attached forms – additional local requirements may also apply.	For local tracking purposes:
Submit completed form to Local Unit of Government (LUG) and system owner within 15 days	
System Status	
System status on date (mm/dd/yyyy): <u>8/20/2018</u>	
_ · · _	npliant – Notice of Noncompliance rade Requirements on page 3)
Reason(s) for noncompliance (check all applicable)	
Impact on Public Health (Compliance Component #1) – Imminent threat to	public health and safety
Other Compliance Conditions (Compliance Component #3) – Imminent thr	eat to public health and safety
☐ Tank Integrity (Compliance Component #2) – Failing to protect groundwat	er
Other Compliance Conditions (Compliance Component #3) – Failing to pro	tect groundwater
Soil Separation (Compliance Component #4) – Failing to protect groundwa	ater
Operating permit/monitoring plan requirements (Compliance Component #	t5) – Noncompliant

Property Information

Parcel	ID# or Sec/Twp/Range:	

Property address: 7723	66th St N, Pine Springs, MN 55115	Reason for inspection:	Property Transfer	
Property owner: Mike N	eely	Owner's phone:		
or				
Owner's representative:		Representative phone:		
Local regulatory authority: Washington County		Regulatory authority pho	ne: <u>651-430-6655</u>	
Brief system description:	Pre-cast septic tank, a pre-cast lift tank, and a r	ock trench drainfield.		
Commonto or recommond	ationa:			

Comments or recommendations:

Certification

wq-wwists4-31 • 1/24/12

I hereby certify that all the necessary information has been gathered to determine the compliance status of this system. No determination of future system performance has been nor can be made due to unknown conditions during system construction, possible abuse of the system, inadequate maintenance, or future water usage.

Inspector name:	Brian H	-lumpal/Christo	phe	r Uebe		Certification number:	С	5342/C9852
Business name:	Inspec	t Minnesota, M	idw	est Soil Testing		License number:	L	2896
Inspector signatur	re:	Brian ;	Yu	mpal After	_//	Phone number:	6	51-492-7550
Necessary or	Loca	lly Require	d A	ttachment	s			
🛛 Soil boring lo	ogs	🛛 Syst	em//	As-built drawing		Forms per local ordinar	ce	
☑Other information	ation (lis	t): Disclaime	er, L	icense				
www.pca.state.mn.	us •	651-296-6300	•	800-657-3864	•	TTY 651-282-5332 or 800-657-3864	•	Available in alternative formats

Impact on Public Health - Compliance component #1 of 5 1.

Compliance criteria:		Verification method(s):
System discharge sewage to the ground surface.	🗌 Yes 🛛 No	Searched for surface outletSearched for seeping in yard/backup in home
System discharge sewage to drain tile or surface waters. System cause sewage backup into dwelling or establishment.	□ Yes ⊠ No □ Yes ⊠ No	 Excessive ponding in soil system/D-boxes Homeowner testimony (See Comments/Explanation) "Black soil" above soil dispersal system System requires "emergency" pumping Deformed due test
Any "yes" answer above indicate an Imminent Threat to Public Hea		 Performed dye test Unable to verify (See Comments/Explanation) Other methods not listed (See Comments/Explanation)
Comments/Explanation:		

2. Tank Integrity – Compliance component #2 of 5

Compliance criteria:		Verification me
System consists of a seepage pit, cesspool, drywell, or leaching pit.	🗌 Yes 🖾 No	Probed tank(sExamined con
Seepage pits meeting 7080.2550 may be compliant if allowed in local ordinance.		Examined Tar
Sewage tank(s) leak below their designed operating depth.	🗌 Yes 🖾 No	 Observed liqui Examined emp
If yes, which sewage tank(s) leaks:		Probed outside
Any "ves" answer above indi	Unable to veri	

system is Failing to Protect Groundwater.

Comments/Explanation:

None of the above found.

thod(s):

-) bottom
- struction records
- nk Integrity Form (Attach)
- id level below operating depth
- pty (pumped) tanks(s)
- e tank(s) for "black soil"
- fy (See Comments/Explanation)
- Other methods not listed (See Comments/Explanation)

3. Other Compliance Conditions – Compliance component #3 of 5

a.	Maintenance hole covers are damaged, cracked, unsecured, or appear to structurally unsound.	🗌 Yes*	🛛 No	🗌 Unknown
----	---	--------	------	-----------

b. Other issues (electrical hazards, etc.) to immediately and adversely impact public health or safety. 🗌 Yes* 🛛 No 📋 Unknown *System is an imminent threat to public health and safety

Explain:

System is non-protective of ground water for other conditions as determined by inspector Yes* 🛛 No C. *System is failing to protect groundwater

Explain:

4. Soil Separation – Compliance component #4 of 5

Date of installation: 1983	Unknov	vn	Ve	erification method(s):	
Shoreland/Wellhead protection/Food Beverage Lodging?	🛛 Yes 🗌] No	Soil observation does not expire. Previous soil observations by two independent parties are suff		
Compliance criteria:			un	less site conditions have been alte	
For systems built prior to April 1, 1996, and not located in Shoreland or Wellhead Protection Area or not serving a food, beverage or lodging establishment:	☐ Yes [] No	 requirements differ. Conducted soil observation(s) (Attach boring Two previous verifications (Attach boring logs Not applicable (Holding tank(s), no drainfield) 		h boring logs)
Drainfield has at least a two-foot vertical separation distance from periodically saturated soil or bedrock.				Unable to verify (See Comments/E Other (See Comments/Explanation)	Explanation)
Non-performance systems built April 1, 1996, or later or for non-performance systems located in Shoreland or Wellhead Protection Areas or serving a food, beverage, or lodging establishment:	🗌 Yes 🛛	🛾 No	Co	mments/Explanation:	
Drainfield has a three-foot vertical separation distance from periodically saturated soil or bedrock.*					
"Experimental", "Other", or "Performance"	□ Yes □ No		In	dicate depths of elevations	
systems built under pre-2008 Rules; Type IV or V systems built under 2008 Rules (7080. 2350 or 7080.2400 (Advanced Inspector License required)			<u>A.</u>	Bottom of distribution media	See Attached Boring Log(s
Drainfield meets the designed vertical separation distance from periodically saturated soil or bedrock.				Periodically saturated soil/bedrock System separation	
			D.	Required compliance separation*	
Any "no" answer above indicates the Failing to Protect Groundwater.	he systen	n is		ay be reduced up to 15 percent if rdinance.	allowed by Loca
Operating Permit and Nitrogen B	MP* – Cor	nplianc	e comp	oonent #5 of 5 🛛 🛛 Not appl	icable
s the system operated under an Operating Peri	mit? [Yes	🛛 No	If "yes", A below is required	
s the system required to employ a Nitrogen BM	P? [] Yes	🛛 No	If "yes", B below is required	
BMP=Best Management Practice(s) specifi					

If the answer to both questions is "no", this section does not need to be completed.

Compliance criteria

a.	Operating Permit number:	🗌 Yes 🔲 No
	Have the Operating Permit requirements been met?	
b.	Is the required nitrogen BMP in place and properly functioning?	🗌 Yes 🗌 No

Any "no" answer indicates Noncompliance.

Upgrade Requirements (Minn. Stat. § 115.55) An imminent threat to public health and safety (ITPHS) must be upgraded, replaced, or its use discontinued within ten months of receipt of this notice or within a shorter period if required by local ordinance. If the system is failing to protect ground water, the system must be upgraded, replaced, or its use discontinued within the time required by local ordinance. If an existing system is not failing as defined in law, and has at least two feet of design soil separation, then the system need not be upgraded, replaced, or its use discontinued, notwithstanding any local ordinance that is more strict. This provision does not apply to systems in shoreland areas, Wellhead Protection Areas, or those used in connection with food, beverage, and lodging establishments as defined in law.

72,07 ĴΈ Juck

Log Of Soil Borings

Locati	ion of Project:	7723 66th Street N,	Pine Springs	MN 55115	
		Inspect Minnesota		Date:	8/20/18
		Hand/Bucket	Classif	ication System:	USDA
Bo	oring Number:	1		Boring Number:	
Surface Elevation of Boring	Same grou	und surface as last nfield trench	Surface Elevation o Boring		
Depth In Inches	Soils E	ncountered	Depth In Inches	Soils En	ncountered
0-18 18-21 21-40 40-50 7.	10YR 3/2 Fine ≈20% Ro 10YR 4/4 Loa 7.5YR 5/8 8 10YR 4/4 Loa	/2 Fine Sand e Sand With Gravel ock Fragments my Fine Sand With a 10YR 7/3 Redox my Fine Sand With 7/3, & 10YR 6/2 Redox			
21" De	pth To End Of B	oring Or Redox	D	epth To End Of Bo	oring Or Redox
Same Ele	evation Of Borin	g Relative To System	E	levation Of Boring	Relative To System
	pth To Bottom (Separation	Df Distribution Media		Pepth To Bottom O of Separation	f Distribution Media
En	d Of Boring At:	50"	E	End Of Boring At:	
	dox Present At:	21"		Redox Present At:	
	ater Present At:			Water Present At:	

Bottom Of Distribution Medium At: 36 Inches

DISCLAIMER

Brian L. Humpal, Inc. dba. Inspect Minnesota, Midwest Soil Testing

Relative to Subsurface Sewage Treatment System (SSTS) Compliance Inspections

- 1. This inspection/report is being performed for only the seller/owner of the property on which the SSTS is located. In such case that another party is paying for the inspection, the contract is between only said party and Brian L. Humpal, Inc.; there is no contract between Brian L. Humpal, Inc. and any other party unless otherwise noted.
- 3. Brian L. Humpal, Inc. has not been retained to warranty, guarantee, or certify the proper functioning of the SSTS for any period of time beyond the date of inspection or into the future. Because of the numerous factors (usage, maintenance, soil characteristics, previous failures, etc.) which may affect the proper operation of an SSTS, as well as the inability of Brian L. Humpal, Inc. to supervise or monitor the use or maintenance of the SSTS, the report shall not be construed as a warranty by Brian L. Humpal, Inc. that the SSTS will function properly for any particular party for any period of time.
- 4. Brian L. Humpal, Inc. is unable to verify the frequency and/or, quality of prior or future maintenance of the SSTS. Maintenance of the tank(s) must be performed through the tanks maintenance hole. The removal of solids from any location other than the maintenance hole is not a compliant method of maintenance. It is strongly recommended that maintenance covers be made accessible to the ground surface to facilitate proper maintenance.
- 5. Minimum Compliance Inspection requirements relative to this inspection and this report include <u>only</u> verification that the SSTS has tank(s) (septic tanks, lift tanks, dosing tanks, stilling tanks, etc.) which are watertight below the designed operating depth, the required separation between the bottom of the subsurface soil distribution medium and seasonally saturated soils, no back-ups of sewage into the dwelling, no discharge of sewage/effluent to the ground surface or surface waters, and no imminent safety hazards. Brian L. Humpal, Inc. does not inspect plumbing or pumps prior to the first SSTS component as these are plumbing components. The performance of exterior pumps and associated components are not inspected as they are considered to be maintenance items. Additionally, no indications relative to compliance with electrical code requirements have been made. It is recommended that any other applicable plumbing, electrical, housing, etc. inspections be performed by a qualified inspection business. Sewage back-up verification is limited to observing the floor drain area and/or the information supplied by the last occupants of the building prior to inspection. Brian L. Humpal, Inc. cannot guarantee that the information given to them by the last occupants of the building prior to inspection relative to back-ups is accurate.
- 4. Certification of this SSTS does not warranty future use beyond the date of the inspection. Any SSTS, old or new, can become hydraulically overloaded or discharge sewage/effluent to the ground surface as a result of more people moving into the house than were previously occupying the house, improper maintenance, heavy usage, leaking plumbing fixtures, groundwater infiltration, tree roots, freezing conditions, surface drainage problems, poor initial design, poor construction practices, or unsuitable materials used in constructing the system; the system can also simply stop working because of its age. An SSTS that has been properly designed and installed, properly maintained, and used in the manner for which the system was designed can be expected to provide service for twenty to twenty-five years on average. Some parts of the SSTS such as alarms, switches, pumps, filters, etc. will most likely have to be repaired or replaced over the lifetime of the system.
- 5. A Compliance Inspection is not meant to be a test or inspection for longevity of the system; a Compliance Inspection is strictly for the purpose of determining if the SSTS is protective of public health and safety, as well as the groundwater at the date and time the inspection was performed. This inspection is not intended to determine if the SSTS was originally designed or installed to past or present MPCA or other Local Government Unit code requirements. This inspection is not intended to determine if the SSTS was designed and/or installed to support the anticipated flow from the building as the use of the building may have changed since the design and construction of the SSTS due to the addition of bedrooms, occupants, etc. In addition, this inspection is not intended to determine the quality of the original SSTS design, the quality of the construction practices used while installing the SSTS, or the quality of the materials used in constructing the SSTS.
- 6. Brian L. Humpal, Inc. cannot guarantee the performance of SSTS products/components such as: gravelless pipe, chamber trenches, effluent filters, tanks, sewage pre-treatment components, piping, etc. Products such as gravelless pipe are no longer approved for installation in the State of Minnesota and may have a significantly reduced performance and/or life expectancy.
- 7. WINTER WORK: By accepting this report, it is understood that inspections conducted during winter months (approximately November 1st through April 1st) are more difficult to perform because of possible snow cover and/or ground frost. SSTS components such as tanks, maintenance covers, tank inspection pipes, subsurface distribution medium inspection pipes, and soil treatment areas are more difficult or impossible to locate due to snow cover and/or ground frost. In addition, soil borings are more difficult to perform due to snow cover and/or ground frost. Brian L. Humpal, Inc. will attempt to use the same level of standards when performing work during winter periods as when performing work during non-winter periods. However, the recipient of this report understands that because of the aforementioned considerations, the same level of standards may not be possible.
- 8. By accepting this report, the client understands that Brian L. Humpal, Inc. will not be responsible for any monetary damages exceeding the fee for the services provided.

Subsurface Sewage Treatment Systems Non-transferable Business License

Inspect Minnesota, Midwest Soil Testing

License # L2896

License Expires: 12/22/2018

Issued: 10/10/2017

Specialty Area(s):

Installer Maintainer Service Provider Advanced Designer Advanced Inspector

Designated Certified Individual(s):

Cert #	Name	Certification Expires:
C9633	Anthony P Scully	7/28/2018
	Installer, Designer (Conditional)
C5342	Brian L Humpal	10/15/2020
	Installer, Maintainer, Serv Prov	, Adv Designer, Adv Inspector
C9852	Christopher R Uebe	3/4/2018
	Designer, Inspector	

MINNESOTA POLLUTION CONTROL AGENCY

520 Lafayette Road North St. Paul, Minnesota 55155-4194

Charles K Thompson, Supervisor Certification & Training Unit