

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

	Systemiciation
Address 11747 239th st n	Telephone Number (4) 238 95
City Scandia	State mn ZIP 55073 Property ID No./GEO Code
Owner robert nitschke	Pumping Date Aug 21, 2018
	Contractor
Maintainer row sewer	MPCA License No. 13309 Telephone Number (651) 465-5505
What was done to the system? Tank(s) Pumped Sludge and scum measured. Do tanks need to be pumped?	Tank 1: 1,200 X Pumped Tank 2: Pump Tank 3: Pumped Tank 4: Pump
Yes No (If no provide measurements	ts below) Total Gallons Pumped: 1,200
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
*Tank Weasurements-Use Only If Tank(s) Were NOT Pamped	
Tank Length in. X Tank Width	in. X Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius	in. X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = 1	Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch
Sludge Level in. X Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. X Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / L	Liquid Capacity = Percent Sludge and Scum in Tank %
Scum Layer	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less tha 12 inches from the bottom of the outle
Effluent Sludge Layer	Tank Depth measured from invert of outlet pipe to bottom of tank baffle; or 2. Total sludge and scum volume is greathan 25 percent of the tank's liquid capacity.
Signature Signature	Date 621(8) Reset Form