

Signature

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

**GOVERNMENT CENTER** 

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location System Location			
Address 20846 Locton	AVer		Telephone Number
City Marind		ZIP Prop	perty ID No./GEO Code
Owner Dean Barr	Pumping Date	10-4-18	
Contractor			
Maintainer Olsons soul	MPCA License I	No.	Telephone Number
What was done to the system?			rt Liquid Capacity in Gallons
Tank(s) Pumped Sludge and scum measured. Do tanks need to be pumped? Yes No (If no provide measurement) Visual Inspection (note any problems with)		Tank 3: [ Total Gallons Pump	Pumped Tank 2: Pumped  Pumped Tank 4: Pumped
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped			
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)			
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)			
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch			
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons			
in. <b>X</b> Gallons Per Inch = Scum Volume Gallons			
Sludge Volume + Scum Volume = Total Sludge and Scum Volume Gallons			
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %			
Scum Layer Effluent Sludge Layer	from	c Depth measured n invert of outlet to bottom of tank	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than  12 inches from the bottom of the outlet baffle; or  2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.
Signature	Date		Reset Form