

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

V6768×1713

System Lo	cation
Address 21474 Hockstra A	vc. N. Telephone Number 7632446897
City Forest Lake StateMNZ	IPSSDD CProperty ID No./GEO Code
Owner Pat Porown Pumping Date	12/4/15
Contractor	
Maintainer Boss Pumping . MPCA License N	lo. 1945 Telephone Number (651) 466-0800
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 1500 Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)	Total Gallons Pumped: 1500
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
	н
	* •
	a a a
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Gallons/Inch	
Tank Volume (cd. III.)	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. X Gailons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total Sludge and Scum Volume Gallons	
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
fron	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.
Signature Date 17-4-15 Reset Form	