

Signature

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006

Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 12860 40th SFS	Telephone Number
* * * * * * * * * * * * * * * * * * *	ZIP 5500/ Property ID No./GEO Code
Owner Laure Cours Pumping Date 2/21/15	
Contractor	
Maintainer MEYER SEWER MPCA Licens	se No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 10000 Temped Tank 2: 15000 A Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)	Total Gallons Pumped: 2500
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
FRE Color (Vine 1)	
	JAN 0.5 20%
377.1 V U 7 U 10	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank	Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. X Gallons Per Inch = Sludge	e Volume Gallons
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total S	Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity	= Percent Sludge and Scum in Tank %
Emuent	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.

Date

Reset Form