

Signature

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006

Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		Syste	m Location			
Address 8450	2 Lafton A	ul		Telephone Number		
City Stilla	enter	State /	1/1P 55083 P	roperty ID No./GEO Code		
Owner Rob	2 Survey	Pumping I				
Contractor						
Maintainer MEY	ER SEWER	MPCA Lice	nse No. 915	Telephone Number 651-459-6	16.	
What was done to the system?			Re	Report Liquid Capacity in Gallons		
Tank(s) Pumped			Tank 1: 130	Pumped Tank 2:	ped	
Sludge and scum measured.			Tank 3:	Pumped Tank 4: Pum	ped	
Do tanks need to be pumped?						
Yes N	o (If no provide measurem	ents below)	Total Gallons Pur	mped: <u>/\$00</u>		
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.						
			RECEIVE			
			JAN 0 5 2016	i ·		
:		a*	All des a con-			
			PUBLIC HEA	The feet		
	*Tank Me	asurements-Use (Only If Tank(s) Were N	OT Pumped		
Tank Length	in. X Tank Width	in. X Tar	nk Depth in.	Tank Volume (cubic inches)		
Tank Radius	in. 🗶 Tank Radius	in. X 3.	14 = Tank Volume (c	ubic inches)		
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch						
Tank Volume (cu. in.) / 25 1.01 — Elquid Capacity Gallons / Tank Depth In. 2 dations / In.						
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons						
Scum Level in. X Gallons Per Inch = Scum Volume Gallons						
Sludge Volume	− + Scum Volume	= Total	Sludge and Scum Volu	me Gallons		
Total Sludge and Sc	um Volumo	/ Liquid Capacity	= Parcar	nt Sludge and Scum in Tank %		
Total Studge and Sc		7 Elquid Capacit	y	R Studge and Sedim in Turk		
	in a little of the second	Ħ		*Tanks must be pumped if either of the following conditions exist:	ne	
				1. The top of the sludge layer is less th	าลท	
Scum Layer H				12 inches from the bottom of the outlet		
Effluent			Tank Depth measured	baffle; or 2. Total sludge and scum volume is g	reatei	
			from invert of outlet pipe to bottom of tank	than 25 percent of the tank's liquid		
Sludge Layer		9	Pipe to pottorn or tank	capacity.		
<u> </u>						

Date

Reset Form