

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location (
Address /7 C/1/ Harris Stear	Au 1	Telephone Number
City Late	State ZIP Pro	perty ID No./GEO Code
Owner (1/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2		
Contractor		
Maintainer A & B Sanitation MPCA License No. Telephone Number (651) 464-2150		
What was done to the system?	Rep	ort Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1; 100 d	Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3:	Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)	Total Gallons Pum	ped: 1000
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.		
		,
	1	•
To be the Collett Tord/o) Ware NOT Pumped		
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped		
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)		
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)		
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch		
Sludge Level in. X Gallons Per Inch	= Sludge Volume Gall	ons .
Scum Level in. X Gallons Per Inch = Scum Volume Gallons		
Słudge Volume + Scum Volume	= Total Sludge and Scum Volum	ne Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %		
		*Tanks must be pumped if either of the
		following conditions exist:
Scum Layer	1	 The top of the sludge layer is less than inches from the bottom of the outlet
	Tank Depth measured	baffle; or
Effluent distribution of the control	from invert of outlet	Total sludge and scum volume is greate than 25 percent of the tank's liquid
Sludge Layer	pipe to bottom of tank	capacity,
	an fire of the second	
	· ·	Don't Farmer
Signature / S (Acc)	Date	Reset Form