

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location		
Address 10005 faciliso 11		Telephone Number
City Glast	State MZIP Prope	erty ID No./GEO Code
Owner On Coll	Pumping Date 12/5/15	
Contractor		
Maintainer A & B Sanitation	MPCA License No. 3855	Telephone Number (651) 464-2150
What was done to the system?	Repor	t Liquid Capacity in Gallons
Tank(s) Pumped Sludge and scum measured. Do tanks need to be pumped? Yes No (If no provide measurements below) Visual Inspection (note any problems with the s	Tank 3: Total Gallons Pumpe	Pumped Tank 2: 300 Pumped Pumped Tank 4: Pumped ed: 1800 s not serve as a compliance inspection.
*Tank Measuréments-Use Only If Tank(s) Were NOT Pumped		
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)		
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)		
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch		
Sludge Level in. X Gallons Per Inch	== Siudge Volume Galion	S .
Scum Level in. X Gallons Per Inch	= Scum Volume Gallon	s
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume	Gallons
Total Sludge and Scum Volume / Liqu	uid Capacity = Percent 5	ludge and Scum in Tank%
Scum Layer Effluent Sludge Layer	Tank Depth measured from invert of outlet pipe to bottom of tank	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.
Signature	Date	Reset Form