

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006

Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location	
Address 10127 -1704 5+N	Telephone Number
City Huse State	ZIP Property ID No./GEO Code
Owner Chils (espie Pumping Date 12/17/15	
Contractor	
Maintainer A & B Sanitation MPCA License No. 3 F5 Telephone Number (651) 464-2150	
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 500 Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped?	Total Gallons Pumped: \Sold
Yes No (If no provide measurements below)	
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. <b>X</b> Gallons Per Inch = Sludge	Volume Gallons .
Scum Level in. <b>X</b> Gallons Per Inch = Scum V	Volume Gallons
Sludge Volume + Scum Volume = Total Sl	ludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
fr	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.
Signature Dat	te Reset Form