

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location		
Address 1444 Lincoln Town	Ave 1	Telephone Number
City Wohlomed. State MM ZIP Property ID No./GEO Code		
Owner Soft Miles Pumping Date 12/3/15		
Contractor		
Maintainer A & B Sanitation MPCA License No. Telephone Number (651) 464-2150		
What was done to the system?	i	t Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 1000	Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3:	Pumped Tank 4: Pumped
Do tanks need to be pumped?  Tyes No (If no provide measurements below)	Total Gallons Pumpe	d: 2000
		not serve as a compliance inspection.
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.		
	•	
		·
		·
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped		
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)		
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)		
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch		
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons		
Scum Level in. <b>X</b> Gallons Per Inch	= Scum Volume Gallon	s
Sludge Volume + Scum Volume =	= Total Sludge and Scum Volume	Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %		
Scum Layer  Effluent  Sludge Layer	Tank Depth measured from invert of outlet pipe to bottom of tank	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than  12 inches from the bottom of the outlet baffle; or  2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.
Signature / 7 / Au	, Date	Reset Form