

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address /6/11/ 3/20 5+. N	Telephone Number
City Lakzland	State M N ZIP 550 43 Property ID No./GEO Code
Owner Janet Conroy	Pumping Date 16/27/14
Contractor	
Maintainer MEYER SEWER	MPCA License No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1:/200 Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped?	Total Gallons Pumped: 1200
Yes No (If no provide measurements b	Elow
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
*Tank Measurements-Use Only if Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius	in. X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Li	iquid Capacity Gallons / Tank Depth in. = Gallons/Inch
Sludge Level in. X Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. X Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Lie	quid Capacity = Percent Sludge and Scum in Tank %
	*Tanks must be pumped if either of the
	following conditions exist:
Scum Layer -	1. The top of the sludge layer is less than 12 inches from the bottom of the outlet
	Tank Denth measured baffle; or
Effluent	from invert of outlet 2. Total studge and scum volume is greater than 35 parcent of the tack's liquid
Sludge Layer	pipe to bottom of tank capacity.
ANCIOLES SOS OSPISOS EN ELECTRICADOS ESPASOS EN ELECTRICADOS E	
	Para Zala - /ul Reset Form