

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

**GOVERNMENT CENTER** 

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## **SSTS MAINTENANCE REPORT**

	System Location	
Address 7785 Quadrant	Au S	Telephone Number
City Hastings	State AMZIP 5503	Property ID No./GEO Code
Owner Ting Eisenmeng	Pumping Date 7/14/	15-
· ·	Contractor /	
Maintainer MEYER SEWER	MPCA License No. 915	Telephone Number 651-459-016
What was done to the system		Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1:	Pumped Tank 2! OCO Pumped
Sludge and scum measured.  Do tanks need to be pumped?	Tank 3:	Pumped Tank 4: Pumped
Yes No (If no provide measurer	nents below) Total Gallor	ns Pumped: 2000
Visual Inspection (note any problems w	th the system): NOTE: T	his does not serve as a compliance inspection.
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped		
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)		
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)		
Tank Volume (cu, in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch		
	· · · · <u></u>	
Sludge Level in. <b>X</b> Gallons Per Inc	h = Sludge Volume	Gallons -
Scum Level in. <b>X</b> Gallons Per Inc	h = Scum Volume	Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum	Volume Gallons
Total Sludge and Scum Volume	/ Liquid Capacity = P	ercent Sludge and Scum in Tank %
	· · · · · · · · · · · · · · · · · · ·	<del></del>
· 🗇	П	*Tanks must be pumped if either of the following conditions exist:
Scum Layer		1. The top of the sludge layer is less than
	Tank Depth measu	12 inches from the bottom of the outlet baffle; or
Effluent	from invert of out	et 2. Total sludge and scum volume is greater
Sludge Layer	pipe to bottom of	tank than 25 percent of the tank's liquid capacity.
N. MERNATO, CONTROL OF THE PROPERTY OF THE PRO		
Signature	Date 7/14/	//s- Reset Form