

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Lo	cation
Address 1012 Catherda Dr	Telephone Number 768-972 人
City Neuport State MN Z	IP 55055 Property ID No./GEO Code
Owner Sandy Weidt Pumping Date	11/15/14
Contra	
Maintainer MEYER SEWER MPCA License N	No. 915 Telephone Number 651-459-0162
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Tes No (If no provide measurements below)	Total Gallons Pumped: /200
Visual Inspection (note any problems with the system):	NOTE: This does not serve as a compliance inspection.
	No.
*Tank Measurements-Use Only	If Tank(s) Were NOT Pumped
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. X Gallons Per Inch = Sludge Vo	lume Gallons
Scum Level in. X Gallons Per Inch = Scum Volu	
Sludge Volume + Scum Volume = Total Slud	ge and Scam volume
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
	*Tanks must be pumped if either of the
	following conditions exist: 1. The top of the sludge layer is less than
Scum Layer	12 inches from the bottom of the outlet
	Depth measured baffle; or 2. Total sludge and scum volume is greater
from	to bottom of tank than 25 percent of the tank's liquid
Sludge Layer	capacity.
Signature Date	/// Reset Form
Signature Charles	10/15/17