

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

			Syst	em Location	•			
Address 16 Quamwell AUE, S				Telephone Number				
City Lake k	and		State /n	N 219550	43 Prop	perty ID No./0	GEO Code	
Owner Abby	Schl	Emmer	Pumping		0/15-			
σ			C	ontractor				
Maintainer MEY	ER SE	WER	MPCA Lice	ense No. 9 A	5	Telephone 1	lumber 65/	-459-016
What was done to the system?				Report Liquid Capacity in Gallons				
Tank(s) Pumped				Tank 1:	1200 %	Pumped	Tank 2:	Pumpen
Sludge and scum measured.				Tank 3:		Pumped		Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)				Total Ga	dlons Pump	ed: 1200)	decemble
Visual Inspection	·			<u> </u>				nce inspection
							•	•
		*Tank Measu	rements-Use	Only If Tank(s)	Were NOT	Pumped		
Tank Length	in. X T	ank Width	in. X Ta	ink Depth	in. =	Tank Volum	e (cubic inches)	
Tank Radius	in. X Т	ank Radius	in. X 3	.14 = Tank V	olume (cub	ic inches)		
Tank Volume (cu. in	1.)	/ 231.01 =	Liquid Capac	ity	Gallons /	Fank Depth	in. = Gaild	ons/Inch
Sludge Level	in. X G	allons Per Inch	= Sluc	lge Volume	Gallor	าร		
Scum Level	in. X G	allons Per Inch	= Scui	m Volume	 Gallor	าร		
Sludge Volume	+ Se	cum Volume	= Tota	ol Sludge and Sc	um Volume		Gallons	
Total Sludge and So	:um Volume		Liquid Capaci	ty	= Percent S	iludge and S	cum in Tank	%
	_[-					following 1. The top		t: ayer is less than
Scum Layer	_1-3		**		<u> </u>	12 inches baffle; or	from the botto	n of the outlet
Effluent				Tank Depth m from invert of pipe to bottor	outlet	Total sludge and scum volume is greate than 25 percent of the tank's liquid		
Sludge Layer				pipe to bottor		capacity.		