

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		System L	ocation			
Address 9033	Jamaca	Ct. N		Telephone N	lumber	
City Lake	Elmo	State MN	ZIP55042P	roperty ID No./G	EO Code	adi dan dan da 1944-1944 - 1944 - 1944 - 1944 - 1944 - 1944 - 1944 - 1944 - 1944 - 1944 - 1944 - 1944 - 1944 -
Owner Dian	z Rud	Pumping Date	10/2/15			
***		Contra	actor			
Maintainer MEYE	RSEWER	MPCA License	No. 915	Telephone N	lumber 65/-	459-016.
What was	s done to the system?		Re	port Liquid Capacity in Gallons		
Tank(s) Pumped	1		Tank 1: 1000	Pumped	Tank 2:	Pumped
Sludge and scum measured. Do tanks need to be pumped?			Tank 3:	Pumped	Tank 4:	Pumped
Yes No (If no provide measurements below)			Total Gallons Pur	nped: 100	ල ල	_
	note any problems with 1		NOTE: This d	oes not serve	as a complian	ce inspection.
					· · · · · · · · · · · · · · · · · · ·	
	*Tank Measu	rements-Use Only	y If Tank(s) Were N	OT Pumped		
Tank Length	in. X Tank Width	in. X Tank D	epth in. :	= Tank Volume	(cubic inches)	
Tank Radius	in. X Tank Radius	in. X 3.14	= Tank Volume (c	ubic inches)		
Tank Volume (cu. in.)	/ 231.01 =	Liquid Capacity	Gallons	Tank Depth	in. = Gallor	ıs/Inch
Sludge Level	in. X Gallons Per Inch	= Sludge V	olume Gal	lons		
Scum Level	in. X Gallons Per Inch	= Scum Vo	lume Gal	lons		
Sludge Volume	+ Scum Volume	= Total Slu	dge and Scum Volur	ne	Gallons	
Total Sludge and Scur	m Volume /	Liquid Capacity	= Percen	t Sludge and Sc	um in Tank	%
Scum Layer Effluent Sludge Layer		fror	*Tanks must be pumped if eith following conditions exist: 1. The top of the sludge layer is 12 inches from the bottom of to baffle; or 2. Total sludge and scum volunthan 25 percent of the tank's lice capacity.			er is less than of the outlet olume is greater
Signature	U	Date	10/2/15		Reset F	orm