

DELAKIWENT OF SORFIC HEALTH AND FUSIKONWENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 8225 Lamer Ave S	Telephone Number
	ZIP SSOI6 Property ID No./GEO Code
Owner Dan Biscore Pumping Da	, ,
Contractor	
Maintainer MEYER SEWER MPCA License	e No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 1000 Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)	Total Gallons Pumped: LOGO
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank	Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total Sli	udge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank / / / / / / / / / / / / / / / / / / /	
	*Tanks must be pumped if either of the following conditions exist:
	1. The top of the sludge layer is less than
Scum Layer The Company of the Compan	12 inches from the bottom of the outlet baffle; or
	2. Total sludge and scum volume is greate:
Sludge Layer pi	pe to bottom of tank than 25 percent of the tank's liquid capacity.