

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

**GOVERNMENT CENTER** 

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

	** : Systemuodanones	
Address 7740 Field Ridge	kd	Telephone Number
City Rod brenz white Beach		Property ID No./GEO Code
Owner Rod Gren 2 Pumping Date 10-1-15		
M. Inteliner	MPCA License No.	Telephone Number 45/-464~2082
Maintainer Olsons sewer		
What was done to the system?		Report Equid Capacity in Gallons Age and the
Tank(s) Pumped		
Sludge and scum measured.  Do tanks need to be pumped?	Tank 3:	
Yes No (If no provide measurements b	pelow) Total Gallon	s Pumped:
Visual Inspection (note any problems with the	e system): NOTE: TI	nis does not serve as a compliance inspection.
Tank Measurements-Use Only If Tank(ts) Were NOT Pumped		
Tank Length in. X Tank Width	in. <b>X</b> Tank Depth	in. = Tank Volume (cubic inches)
	<u> </u>	<del></del>
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)		
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch		
Sludge Level in. X Gallons Per Inch	= Sludge Volume	Gallons ·
Scum Level in. <b>X</b> Gallons Per Inch = Scum Volume Gallons		
Sludge Volume + Scum Volume = Total Sludge and Scum Volume Gallons		
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %		
		*Tanks must be pumped if either of the
		following conditions exist:  1. The top of the sludge layer is less than
Scum Layer	<u> </u>	12 inches from the bottom of the outlet
Effluent	Tank Depth measur from invert of outle	2. Total sludge and scum volume is greater
Shadon Layer	pipe to bottom of to	than 35 percent of the tank's liquid
Sludge Layer		
Signature	Date /()~/	-/s Alexa to the second