

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		System Lo	cation		
Address UlaiU	170th St Was	24/2		Telephone Number 651-46	12-3438
City Lung	1.10.1.2	,	IP 57038 Pro	perty ID No./GEO Code	
Owner SAM	Abott	Pumping Date	11-13-15		
		Contra	etor		
Maintainer 0\S	on Sever	MPCA License	10.216	Telephone Number 65 (14)	04.2082
What was	idone to the system?	1947 (1948) 1964 - Maria	Repl	ort Liquid Capacity in Gallons	
Pl-Pank(s) Pumped			Tank 1: (UD)	Pumped Tank 2: (しゅ)	X Pumped
Sludge and scum n	neasured.		Tank 3:	Pumped Tank 4:	Pumped
Do tanks need to be pumped?					
	(If no provide measurement			4.55	
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.					
*Tank Measurements-Use Only:If Tank(s):Were NOT Pumped					
Tank Length	in. X Tank Width	in. X Tank De	epth in. =	Tank Volume (cubic inches)	
Tank Radius	in. X Tank Radius	in. X 3.14 :	 Tank Volume (cul 	oic inches)	
Tank Volume (cu. in.)	/ 231.01 =	Liquid Capacity	Gallons /	Tank Depth in. = Gallons	s/Inch
Sludge Level	in. X Gallons Per Inch	= Sludge Vo	olume Gallo	ons	
Scum Level	in. X Gallons Per Inch	= Scum Vol	ume Gallo	ons	
Sludge Volume	+ Scum Volume	= Total Slud	ge and Scum Volum	e Gallons	
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %					
Scum Layer Effluent Sludge Layer		from	Depth measured ninvert of outlet to bottom of tank	*Tanks must be pumped if e following conditions exist: 1. The top of the sludge laye 12 inches from the bottom of baffle; or 2. Total sludge and scum vo than 25 percent of the tank' capacity.	er is less than of the outlet lume is greater
	2		1 1216	Reset/Fig	e company