

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location	
Address 705 Settlers Ridge Telephone Number	
City Was do	ZIP 55 Property ID No./GEO Code
Owner Carol Dimulling Pumping Date	
Contractor	
Maintainer MEYER SEWER MPCA License	No. 915 Telephone Number 651-457-016
What was done to the system?	Report Liquid Capacity in Gallons
Cank(s) Pumped	Tank 1: 1500 Fumped Tank 2: Pumped
Sludge and scum measured.  Do tanks need to be pumped?	Tank 3: Pumped Tank 4: Pumper
Yes No (If no provide measurements below)	Total Gallons Pumped:
Visual Inspection (note any problems with the system):  NOTE: This does not serve as a compliance inspection	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank D	epth in. = Tank Volume (cubic inches)
- PT Theology . Service -	= Tank Volume (cubic inches)
Tank Volume (cu, in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total Sludge and Scum Volume Gallons	
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
Tanks must be pumped if either of the	
	following conditions exist:
Scum Layer	1. The top of the sludge layer is less than 12 inches from the bottom of the outlet
fror	k Depth measured n invert of outlet  baffle; or 2. Total sludge and scum volume is greate than 35 persont of the triples liquid
Sludge I.ayer pip	e to bottom of tank capacity.