

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

Address 1745 City 54 Commer B.	Ramada A	h. <			
- 21 C	my R. L			Telephone Number	
Owner Bill	SLX William	State MI	1 ZIP 5504/3 Pro	perty ID No./GEO Code	
	Glampe.	Pumping Di			
*		Con	tractor		
Maintainer MEY	ER SEWER	MPCA Licens	se No. 915	Telephone Number 651-457-016	
What was done to the system?			Report Liquid Capacity in Gallons		
Tank(s) Pumped			Tank 1: 1000 I Pumped Tank 2: 1000 I Pumper		
Sludge and scum measured.			Tank 3:	Pumped Tank 4: Pumper	
Do tanks need to be pumped?			Total Gallons Pumped: 2 mm		
Yes No (If no provide measurements below)					
Visual Inspection (note any problems with the system):			NOTE: This does not serve as a compliance inspection		
	*Tank Mea	surements lica Or	nly (f Tank(s) Were NOT	*Dump ad	
Tankinger					
Tank Length	in. X Tank Width	in, X Tank	Depth in. =	Tank Volume (cubic inches)	
Tank Radius	in. X Tank Radius	in. X 3.1 4	4 = Tank Volume (cub	ic inches)	
Tank Volume (cu. in) / 231.01 =	= Liquid Capacity	Gallons /	Tank Depth in. = Gallons/Inch	
Sludge Level	in. X Gallons Per Inch	= Sludge	Volume Gallo	ns ———	
Scum Level	in. X Gallons Per Inch		- 		
	The A Odnors Per mon	= Scum V	/olume Gallor		
Sludge Volume	+ Scum Volume -	= Total SI	ludge and Scum Volume	Gallons	
Total Sludge and Sc	um Volume	/ Liquid Capacity	= Percent S	Sludge and Scum in Tank %	
				Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet	