Inspect Minnesota & Midwest Soil Testing

P.O. Box 10853 White Bear Lake, MN 55110 651-492-7550/Brian@Midwestsoiltesting.com

Brian Humpal

MPCA Licensed Advanced Inspector

SUBSURFACE SEWAGE TREATMENT SYSTEM (SSTS) COMPLIANCE REPORT

Inspection Address: 9090 Jamaca Ct N, Lake Elmo, MN 55042

REPORT SUMMARY

I have performed an "MPCA Compliance Inspection" on this system and have reviewed the records provided by the homeowner. This system consists of two pre-cast septic tanks, a precast lift tank, and a seepage bed.

Predicated on my inspection of the system and my review of the records, it is my opinion that this system <u>presently meets</u> MPCA minimum compliance inspection requirements.

Inspect Minnesota and Midwest Soil Testing have been hired to perform a compliance inspection of this SSTS for compliance with local ordinances pursuant to Minn. Stat. § 115.55 (2013). This compliance inspection covers only the criteria required by Minn. Stat. § 115.55 Subd. 5a (2013) and Minn. R. 7080.1500 (2011). A compliance inspection is an indication of the current compliance status of the system and does not guarantee the performance or longevity of this system beyond the date of inspection, as it is impossible to determine the future performance of any system. Inspect Minnesota and Midwest Soil Testing disclaim any use of this compliance inspection beyond determining SSTS compliance pursuant to Minn. Stat. § 115.55 Subd. 5a (2013) and Minn. R. 7080.1500 (2011).

Please contact me should you have any questions.

Christopher Uebe

Brian Humpal

Brian Humpal



Compliance Inspection Form

Existing Subsurface Sewage Treatment Systems (SSTS)

Doc Type: Compliance and Enforcement

Instructions: Inspection results based on Minnesota Pollution Control Agency (MPCA) requirements and attached forms – additional local requirements may also apply.	For local tracking purposes:				
Submit completed form to Local Unit of Government (LUG) and system owner within 15 days					
System Status					
System status on date (mm/dd/yyyy):7/18/2019					
· · · · · · · · · · · · · · · · · · ·	npliant – Notice of Noncompliance rade Requirements on page 3)				
Reason(s) for noncompliance (check all applicable) Impact on Public Health (Compliance Component #1) – Imminent threat to public health and safety Other Compliance Conditions (Compliance Component #3) – Imminent threat to public health and safety Tank Integrity (Compliance Component #2) – Failing to protect groundwater Other Compliance Conditions (Compliance Component #3) – Failing to protect groundwater Soil Separation (Compliance Component #4) – Failing to protect groundwater Operating permit/monitoring plan requirements (Compliance Component #5) – Noncompliant					
Property Information Parcel ID# or Sec/Twp/Range	ie:				
	or inspection: Property Transfer				
Property owner: Pete Klopp Owner's p	phone:				
Owner's representative: Represen	tative phone:				
Local regulatory authority: Washington County Regulator	Regulatory authority phone: 651-430-6655				
Brief system description:	ge bed.				
Comments or recommendations:					
Certification					
I hereby certify that all the necessary information has been gathered to determine the compliance status of this system. No determination of future system performance has been nor can be made due to unknown conditions during system construction, possible abuse of the system, inadequate maintenance, or future water usage.					
Inspector name: Brian Humpal/Christopher Uebe Certificati	on number: <u>C5342/C9852</u>				
Business name: Inspect Minnesota, Midwest Soil Testing Licen	se number: L2896				
Inspector signature: Brian Humpal for the Pho	ne number: 651-492-7550				
Necessary or Locally Required Attachments					
	local ordinance				
☑ Other information (list): Report Summary, Property Information, Disclaimer, Lic					

www.pca.state.mn.us • 651-296-6300 • 800-657-3864 • TTY 651-282-5332 or 800-657-3864 • Available in alternative formats wq-wwists4-31 • 1/24/12 Page 1 of 3

Property address: 9090 Jamaca Ct N, Lake Elmo, MN 55042

Inspector initials/Date: 7/18/2019 24 (1)

Impact on Public Health – Compliance component #1 of 5 Compliance criteria: Verification method(s): Searched for surface outlet ☐ Yes ☐ No System discharge sewage to the Searched for seeping in yard/backup in home ground surface. System discharge sewage to drain tile ☐ Yes ☐ No ☐ Homeowner testimony (See Comments/Explanation) or surface waters. ☐ "Black soil" above soil dispersal system ☐ Yes ☐ No System cause sewage backup into ☐ System requires "emergency" pumping dwelling or establishment. ☐ Performed dye test Any "yes" answer above indicates the system is Unable to verify (See Comments/Explanation) an Imminent Threat to Public Health and Safety. Other methods not listed (See Comments/Explanation) Comments/Explanation: None of the above found. 2. Tank Integrity – Compliance component #2 of 5 Verification method(s): Compliance criteria: Probed tank(s) bottom System consists of a seepage pit, ☐ Yes ☐ No cesspool, drywell, or leaching pit. Seepage pits meeting 7080.2550 may be ☐ Examined Tank Integrity Form (Attach) compliant if allowed in local ordinance. ☐ Observed liquid level below operating depth ☐ Yes ☒ No Sewage tank(s) leak below their ☐ Examined empty (pumped) tanks(s) designed operating depth. ☐ Probed outside tank(s) for "black soil" If yes, which sewage tank(s) leaks: ☐ Unable to verify (See Comments/Explanation) Any "ves" answer above indicates the ☑ Other methods not listed (See Comments/Explanation) system is Failing to Protect Groundwater. Comments/Explanation: Lowered underwater camera into tanks - baffles and tank walls OK. Lift pump and alarm were operational at the time of the inspection. 3. Other Compliance Conditions – Compliance component #3 of 5 Maintenance hole covers are damaged, cracked, unsecured, or appear to structurally unsound. ☐ Yes* ⊠ No ☐ Unknown a. Other issues (electrical hazards, etc.) to immediately and adversely impact public health or safety.

Yes* No ☐ Unknown *System is an imminent threat to public health and safety Explain: System is non-protective of ground water for other conditions as determined by inspector ☑ No *System is failing to protect groundwater Explain:

www.pca.state.mn.us • 651-296-6300 • 800-657-3864 • TTY 651-282-5332 or 800-657-3864 • Available in alternative formats wq-wwists4-31 • 1/24/12 Page 2 of 3

Pro	perty address: 9090 Jamaca Ct N, Lake Elmo,	MN 55042	2	Inspector initials/Date: _7	/18/2019 BH ()
4.	Soil Separation – Compliance compor	nent #4 of	⁻ 5		
	Date of installation: 2005 Shoreland/Wellhead protection/Food Beverage Lodging? Compliance criteria:	☐ Yes ☒ No S		Verification method(s): Soil observation does not expire. Previous soil observations by two independent parties are sufficient, unless site conditions have been altered or local	
	For systems built prior to April 1, 1996, and not located in Shoreland or Wellhead Protection Area or not serving a food, beverage or lodging establishment: Drainfield has at least a two-foot vertical separation distance from periodically saturated soil or bedrock.	Yes	□ No	requirements differ. ☐ Conducted soil observation(s) ☐ Two previous verifications (Attain the control of the	(Attach boring logs) ach boring logs) no drainfield) s/Explanation)
	Non-performance systems built April 1, 1996, or later or for non-performance systems located in Shoreland or Wellhead Protection Areas or serving a food, beverage, or lodging establishment:	⊠ Yes	□ No	Comments/Explanation: Reviewed design and permit recor	rds.
	Drainfield has a three-foot vertical separation distance from periodically saturated soil or bedrock.*				
	"Experimental", "Other", or "Performance" systems built under pre-2008 Rules; Type IV or V systems built under 2008 Rules (7080. 2350 or 7080.2400 (Advanced Inspector License required) Drainfield meets the designed vertical separation distance from periodically saturated soil or bedrock.	☐ Yes ☐ No	Indicate depths of elevations See Attached Boring Log(s)		
			-	B. Periodically saturated soil/bedrock System separation	
	Any "no" answer above indicates the system is Failing to Protect Groundwater.		em is	D. Required compliance separation* *May be reduced up to 15 percent if allowed by Local Ordinance.	
5.	Operating Permit and Nitrogen B	MP* – Co	ompliance co	omponent #5 of 5 🔀 Not ap	plicable
	Is the system operated under an Operating Per	mit?	☐ Yes ☐ I	No If "yes", A below is required	I
	Is the system required to employ a Nitrogen BM			No If "yes", B below is required	I
	BMP=Best Management Practice(s) specifi	ied in the s	system design		
	If the answer to both questions is "no",	this sect	ion does no	ot need to be completed.	
	Compliance criteria				
	a. Operating Permit number:			☐ Yes ☐ No	
	Have the Operating Permit requirements b				
	b. Is the required nitrogen BMP in place and properly functioning?			☐ Yes ☐ No	

Any "no" answer indicates Noncompliance.


Upgrade Requirements (Minn. Stat. § 115.55) An imminent threat to public health and safety (ITPHS) must be upgraded, replaced, or its use discontinued within ten months of receipt of this notice or within a shorter period if required by local ordinance. If the system is failing to protect ground water, the system must be upgraded, replaced, or its use discontinued within the time required by local ordinance. If an existing system is not failing as defined in law, and has at least two feet of design soil separation, then the system need not be upgraded, repaired, replaced, or its use discontinued, notwithstanding any local ordinance that is more strict. This provision does not apply to systems in shoreland areas, Wellhead Protection Areas, or those used in connection with food, beverage, and lodging establishments as defined in law.

TTY 651-282-5332 or 800-657-3864 • Available in alternative formats www.pca.state.mn.us • 651-296-6300 • 800-657-3864 Page 3 of 3

Inspect Minnesota & Midwest Soil Testing Subsurface Sewage Treatment System Owner/Property Information This information will be used for the nurpose of conducting an MPCA Compliance Inspection

This information will be used for the purpose of conducting an MPC	A Computance inspection.			
Date of Inspection: July 18, 2019	Time: 9:15 AM			
Property Address: 9090 Jamaca Ct N, Lake Elmo, MN	Zip: 55042			
Property Owner: Pete Klopp	Phone:			
Tank(s) Tank(s)Material Soil Treatment System Septic 2 Fiberglass Rock trench Aerobic Plastic Gravelless trench Lift Metal Chamber trench Holding Concrete Seepage bed Other: Block Mound Other At-grade	Other Alternative system Experimental system Cesspool system Other system			
Are the tank maintenance covers accessible? ⊠ Yes ☐ No *I	f no, proper maintenance must be			
performed through the maintenance holes. Maintenance hole cov				
the ground surface to facilitate access and proper maintenance of	the system.			
Year house built: 1968 Year septic installed: 2005	Tank size (gals.): 2-1000			
How long has seller owned the property? Number of r	esidents in home?			
Number of bedrooms? 4 Are all floors drained by	gravity? Lower Pumped			
Garbage disposal? Whirlpool bath				
More than one system (laundry, etc.)?				
Does this property have any footing drain tiles connected to the s	septic system?			
Are any buildings on this property such as garages or out-buildings connected to this system?				
Are there any additional systems on this property serving other b	uildings?			
Location of septic system on lot? Tanks - North Side, Drainfield	- South Side			
	ne well a deep well? N/A			
Have you ever experienced any problems with the system such as: tree roots, sewage back-ups,				
surfacing of sewage onto the ground, septic tank overflowing, etc.; or have any repairs been made				
to the system? If yes, explain:				
When was the system last pumped? 2018 Name of pur	nper: Pinky's Sewer Service			
How often pumped in previous years?				
Have you received notices from any government agency concerning this system?				
Is your property located in a shoreland management area? N				
Do you have any additional information that should be given to the new owner?				
I hereby certify that the above information is correct to the best of my knowledge. I also understand that if the system is considered "non-compliant/failing" per MPCA rules, that the inspector must by law submit a copy of this report to the local government unit within 15 days of the date of inspection completion. I also agree that unless otherwise noted in				

this report, that I/we are ultimately responsible for payment of all fees for all work performed relative to this inspection by Inspect Minnesota and Midwest Soil Testing.



Log Of Soil Observations

Location of Project: 9090 Jamaca Ct N, Lake Elmo, MN 55042						
Observations Made By: Inspect Minnesota				Date:	7/18/19	
Auger Used: Hand/Bucket		Class	ification System:	USDA		
Soil Observation: 1		Soil Observation:				
Surface Elevation of Observation Same ground surface as seepage bed		Surface Elevation Observation	of			
Depth In Inches	Soils E	ncountered	Denth In			
0-5 5-18 18-36 36-43 43-47 47-58	10YR 3/4 Loamy With 10YR 2/2 10YR 3/4 7.5YR 3/4 Sand ≈15% Rd 7.5YR 4/4 Sand ≈30% Rd	andy Loam (Fill) Sand (Fill/Disturbed) Fill Redox Loamy Sand Loamy Sand Justify Loam With Gravel Loam With G				
58"	Depth To End Of So	oil Observation Or Redox		Depth To End Of So	il Observation Or Redox	
Same	Elevation Of Observation Relative To System			Elevation Of Observa	ation Relative To System	
				Depth To Bottom C	Of Distribution Media	
≥33" Of Separation			Of Separation			
			F 1000	11.01	Ī	
End Of Soil Observation At: 58"		End Of So	oil Observation At:			
Redox Present At: None				Redox Present At:		
Standing Water Present At: None			Standing	Water Present At:		

Bottom Of Distribution Medium At: 25 Inches

Job: <u>9090 Jamaca Ct. N. Lake Elmo</u> Date: <u>7-07-05</u>

137 (2-14) 179				986-998-998-998-998-998-998-998-998-998-
Depth Feet 6-1	\$62	₩-6-3	#B-4	# B-5
Black Loam Top Soil	Dark brown	Black Loam	Dark brown	Dark Bran
17.1	sandy loam Jopsoil	Top Soil	sandy Loan topsoil	512NDY LOUM
Red brown	medium brown	Medium brown	Red brown silt loam 5yr 4/3 15	
medium sand	\$ and y loam 20		Red brown	- Red brown Medium
5yr 4/3	medium brown	mottled at	medium sand	
3 yr 7/3	sendy silt loam	15" down	54r 8/3	SAND
363	36	104r4/3		5yr4/3
Red brown	red brown coarse	. ida		40
Coarse band and gravel 4	5yr 4/3	m - +		Reel brown
5yr 4/3	red brown fine sand		SD	Coorse SAND
60 5	mottled 5yr 4/3		Red brown sandy clay 1 mottled at 50" 5 yr/4	uani _
			MOTTIERAL	
6			<u> </u>	
			* **	
7		·		

DISCLAIMER

Brian L. Humpal, Inc. dba. Inspect Minnesota, Midwest Soil Testing Relative to Subsurface Sewage Treatment System (SSTS) Compliance Inspections

- 1. This inspection/report is being performed for only the seller/owner of the property on which the SSTS is located. In such case that another party is paying for the inspection, the contract is between only said party and Brian L. Humpal, Inc.; there is no contract between Brian L. Humpal, Inc. and any other party unless otherwise noted.
- 3. Brian L. Humpal, Inc. has not been retained to warranty, guarantee, or certify the proper functioning of the SSTS for any period of time beyond the date of inspection or into the future. Because of the numerous factors (usage, maintenance, soil characteristics, previous failures, etc.) which may affect the proper operation of an SSTS, as well as the inability of Brian L. Humpal, Inc. to supervise or monitor the use or maintenance of the SSTS, the report shall not be construed as a warranty by Brian L. Humpal, Inc. that the SSTS will function properly for any particular party for any period of time.
- 4. Brian L. Humpal, Inc. is unable to verify the frequency and/or, quality of prior or future maintenance of the SSTS. Maintenance of the tank(s) must be performed through the tanks maintenance hole. The removal of solids from any location other than the maintenance hole is not a compliant method of maintenance. It is strongly recommended that maintenance covers be made accessible to the ground surface to facilitate proper maintenance.
- 5. Minimum Compliance Inspection requirements relative to this inspection and this report include <u>only</u> verification that the SSTS has tank(s) (septic tanks, lift tanks, dosing tanks, stilling tanks, etc.) which are watertight below the designed operating depth, the required separation between the bottom of the subsurface soil distribution medium and seasonally saturated soils, no back-ups of sewage into the dwelling, no discharge of sewage/effluent to the ground surface or surface waters, and no imminent safety hazards. Brian L. Humpal, Inc. does not inspect plumbing or pumps prior to the first SSTS component as these are plumbing components. The performance of exterior pumps and associated components are not inspected as they are considered to be maintenance items. Additionally, no indications relative to compliance with electrical code requirements have been made. It is recommended that any other applicable plumbing, electrical, housing, etc. inspections be performed by a qualified inspection business. Sewage back-up verification is limited to observing the floor drain area and/or the information supplied by the last occupants of the building prior to inspection. Brian L. Humpal, Inc. cannot guarantee that the information given to them by the last occupants of the building prior to inspection relative to back-ups is accurate.
- 4. Certification of this SSTS does not warranty future use beyond the date of the inspection. Any SSTS, old or new, can become hydraulically overloaded or discharge sewage/effluent to the ground surface as a result of more people moving into the house than were previously occupying the house, improper maintenance, heavy usage, leaking plumbing fixtures, groundwater infiltration, tree roots, freezing conditions, surface drainage problems, poor initial design, poor construction practices, or unsuitable materials used in constructing the system; the system can also simply stop working because of its age. An SSTS that has been properly designed and installed, properly maintained, and used in the manner for which the system was designed can be expected to provide service for twenty to twenty-five years on average. Some parts of the SSTS such as alarms, switches, pumps, filters, etc. will most likely have to be repaired or replaced over the lifetime of the system.
- 5. A Compliance Inspection is not meant to be a test or inspection for longevity of the system; a Compliance Inspection is strictly for the purpose of determining if the SSTS is protective of public health and safety, as well as the groundwater at the date and time the inspection was performed. This inspection is not intended to determine if the SSTS was originally designed or installed to past or present MPCA or other Local Government Unit code requirements. This inspection is not intended to determine if the SSTS was designed and/or installed to support the anticipated flow from the building as the use of the building may have changed since the design and construction of the SSTS due to the addition of bedrooms, occupants, etc. In addition, this inspection is not intended to determine the quality of the original SSTS design, the quality of the construction practices used while installing the SSTS, or the quality of the materials used in constructing the SSTS.
- 6. Brian L. Humpal, Inc. cannot guarantee the performance of SSTS products/components such as: gravelless pipe, chamber trenches, effluent filters, tanks, sewage pre-treatment components, piping, etc. Products such as gravelless pipe are no longer approved for installation in the State of Minnesota and may have a significantly reduced performance and/or life expectancy.
- 7. WINTER WORK: By accepting this report, it is understood that inspections conducted during winter months (approximately November 1st through April 1st) are more difficult to perform because of possible snow cover and/or ground frost. SSTS components such as tanks, maintenance covers, tank inspection pipes, subsurface distribution medium inspection pipes, and soil treatment areas are more difficult or impossible to locate due to snow cover and/or ground frost. In addition, soil borings are more difficult to perform due to snow cover and/or ground frost. Brian L. Humpal, Inc. will attempt to use the same level of standards when performing work during winter periods as when performing work during non-winter periods. However, the recipient of this report understands that because of the aforementioned considerations, the same level of standards may not be possible.
- 8. By accepting this report, the client understands that Brian L. Humpal, Inc. will not be responsible for any monetary damages exceeding the fee for the services provided.

Subsurface Sewage Treatment Systems

Non-transferable

Business License

Inspect Minnesota, Midwest Soil Testing

License # L2896

License Expires: 12/22/2019

Issued: 11/20/2018

Specialty Area(s):

Installer
Maintainer
Service Provider
Advanced Designer
Advanced Inspector

Designated Certified Individual(s):

Cert #	Name	Certification Expires:
C9633	Anthony P Scully	3/5/2020
	Installer, Designer (Apprentice)	
C5342	Brian L Humpal	10/15/2023
	Installer, Maintainer, Serv Prov, Adv	Designer, Adv Inspector
C9852	Christopher R Uebe	3/4/2021
	Designer, Inspector	



520 Lafayette Road North St. Paul, Minnesota 55155-4194 Mich Haig

Nick Haig, Supervisor Certification and Training Unit