

## DEPAKIMENT OF PUBLIC HEALTH AND ENVIKONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

			Sy	/stem Loc	ation				
Address 1790 Racine Are S				Telephone Number					
City St Cro.	8 13	Beach	State	UN ZIF	5504.	<b>3</b> Prop	perty ID No./(	GEO Code	
Owner Bruce	PI	ater	Pumpi	ng Date		1/10-	-		
				Contract	or	// 3			
Maintainer MEY	er s	EWER	MPCA I	icense No	915		Telephone N	lumber 65/	-459-016
What was done to the system?				Report Liquid Capacity in Gallons					
Tank(s) Pumped				Tank 1: Pumped Tank 2: Pump					
Sludge and scum measured.				ì	Tank 3:	<u> </u>	Pumped		Pumped
Do tanks need to be pumped?  Yes No (If no provide measurements below)				Total Gallons Pumped: 15AC					
Visual Inspection (				Ĺ					was inspection
The state of the s		y problems with the	ie system)		NOTE:	mis doe	2 Hor zerve	as a compila	nce inspection
		*Tank Measu	rements-U	se Only If	Tank(s) W	ere NOT	Pumped		
Tank Length	in. X	Tank Width	in. X	Tank Dept	th	in. =	Tank Volume	(cubic inches	)
Tank Radius	in. X	Tank Radius	in. <b>X</b>	3.14 =	Tank Volu	me (cubi	ic inches)		
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch									ons/inch
Sludge Level	in. X	Gallons Per Inch	= SI	udge Volu	me	Gallor	ns	<del></del>	
Scum Level	in. <b>X</b>	Gallons Per Inch	= Sc	tum Volum	 пе	 Gallor	ns		
Sludge Volume	+	Scum Volume	= Tc	otal Sludge	and Scum	 Volume		Gallons	
Total Sludge and Scu	ım Volur	ne / I	Liquid Capa	city	= r	ercent S	ludge and Sc	um in Tank	%
Scum Layer				*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less tha					:
					····	,	12 inches from the bottom of the outlet		
Effluent				from in	epth measured vert of outlet		baffle; or  2. Total sludge and scum volume is greate than 25 percent of the tank's liquid		
Sludge Layer				pipe to	bottom of	tank	capacity.		