

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 11060 7.04h 54. S	Telephone Number
City Cottage GROVE State MW Z	IP550/6 Property ID No./GEO Code
Owner Ed Monthriand Pumping Date 10/21/15	
Contractor	
Maintainer MEYER SEWER MPCA License N	lo. 915 Telephone Number 651-459-016.
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped 2	Tank 1: / 500 Pumped Tank 2: 1000 Pumped
Sludge and scum measured. Do tanks need to be pumped?	Tank 3: Pumped Tank 4: Pumped
Yes No (If no provide measurements below)	Total Gallons Pumped: 2500
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank De	pth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14 =	Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total Slud	ge and scam voidine
Total Sludge and Scum Volume / Liquid Capacity	= Percent Sludge and Scum in Tank %
	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than
Scum Layer —	12 inches from the bottom of the outlet
from	baffle; or 2. Total sludge and scum volume is greater to bottom of tank baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid
Sludge Layer	capacity.

non 10/21/15

Reset Form