

Signatura

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location	
Address 16465 25th SFS	Telephone Number
	Property ID No./GEO Code
Owner Marthe Missour Pumping Date 10 Ses/15-	
Contractor	
Maintainer MEYER SEWER MPCA License N	lo. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: Dune Pumped Tank 2: Com Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped?  Yes No (If no provide measurements below)	Total Gallons Pumped:
Visual Inspection (note any problems with the system):  NOTE: This does not serve as a compliance inspection.	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. <b>X</b> Tank Width in. <b>X</b> Tank De	pth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14 =	= Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity	Gallons / Tank Depth in. = Gallons/Inch
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. <b>X</b> Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total Slud	ge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity	= Percent Sludge and Scum in Tank %
from	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.

Data

Reset Form