

Cionatura

## DELAKIMENT OF LARPIC HEALTH WAD FULLKONWENT

**GOVERNMENT CENTER** 

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

		Syste	em Location		<del></del>	
Address 2450	Trading Post	17/	**************************************	Telephone Number	····	
City Auf Jos	2	State	/ ZIP <b>5500/</b> Prop	erty ID No./GEO Code		
Owner Toold	Havite	Pumping	Date 10/15/5			
		Co	ontractor			
Maintainer MEY	ER SEWER	MPCA Lice	ense No. 915	Telephone Number 651-4	159-016	
What was done to the system?			Report Liquid Capacity in Gallons			
Tank(s) Pumped			Tank 1: Pumped Tank 2: 1000 Pumped			
Sludge and scum measured.  Do tanks need to be pumped?			Tank 3: Pumped Tank 4: Pumped			
Yes No (If no provide measurements below)			Total Gallons Pumped: 2000			
Visual Inspection (	note any problems with th	e system):	NOTE: This doe	s not serve as a compliance	e inspection.	
	*Tank Maasu	amonte llea	Only If Tank(s) Were NOT	Pumped		
			······································			
Tank Length	in. <b>X</b> Tank Width	in. <b>X</b> Ta	nk Depth in. =	Tank Volume (cubic inches)		
Tank Radius	in. <b>X</b> Tank Radius	in. <b>X 3</b> .	.14 = Tank Volume (cub	ic inches)		
Tank Volume (cu. in.)	/ 231.01 =	Liquid Capaci	ity Gallons / 1	Tank Depthin. = Gallons	/Inch	
Słudge Level	in. <b>X</b> Gallons Per Inch	= Slud	ige Volume Gallor	ns		
Scum Level	in. <b>X</b> Gallons Per Inch	= Scur	m Volume Gallor	าร		
Sludge Volume	+ Scum Volume	 = Tota	I Sludge and Scum Volume	Gallons		
Total Sludge and Scu	um Volume / I	iquid Capacit	ty = Percent S	ludge and Scum in Tank	%	
Scum Layer Effluent Sludge Layer			Tank Depth measured from invert of outlet pipe to bottom of tank	*Tanks must be pumped if e following conditions exist: 1. The top of the sludge laye 12 inches from the bottom of baffle; or 2. Total sludge and scum vo than 25 percent of the tank' capacity.	er is less than of the outlet dume is greater	

Dato

Reset Form