

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		Syst	rem Location	
Address 13078	Point Douglag	0-	Telephone Number	
City History			7/ZIP 65033 Property ID No./GEO Code	
Owner Rist	Morris	Pumping	Date 10/6/15	
		C	ontractor	
Maintainer MEY	ER SEWER	MPCA Lic	ense No. 915 Telephone Number 651-459-016	
What was done to the system?			Report Liquid Capacity in Gallons	
Tank(s) Pumped			Tank 1: /Scar Pumped Tank 2: Pumped	
Sludge and scum measured. Do tanks need to be pumped?			Tank 3: Pumped Tank 4: Pumped	
Yes No (If no provide measurements below)			Total Gallons Pumped: LSCIO	
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection				
			•	
			•	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped				
Tank Length	in. X Tank Width	in, X Ta	ank Depth in. = Tank Volume (cubic inches)	
Tank Radius	in. X Tank Radius	in. X 3	.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch				
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons				
Scum Level in. X Gallons Per Inch = Scum Volume Gallons				
	+ Scum Volume			
Sludge Volume ——		= Tota		
Total Sludge and Sc	um Volume / L	iquid Capacii	ty = Percent Sludge and Scum in Tank %	
		=	*Tanks must be pumped if either of the	
			following conditions exist: 1. The top of the sludge layer is less than	
Scum Layer			12 inches from the bottom of the outlet	
Effluent		1	Tank Depth measured baffle; or 2. Total sludge and scum volume is greate:	
Cludes Laure			pipe to bottom of tank than 25 percent of the tank's liquid	
Sludge Layer capacity.			capacity.	