

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

, System Location	
Address 13167 22nd St 1	Telephone Number
	tate MI ZIP 55082 Property ID No./GEO Code
Owner JU/ RUSSe // P	umping Date 18/5/15
Contractor	
Maintainer MEYER SEWER MPCA License No. 915 Telephone Number 651-459-016.	
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped Sludge and scum measured. Do tanks need to be pumped? Yes No (If no provide measurements below	Tank 1: Pumped Tank 2: Pumped Tank 3: Pumped Tank 4: Pumped Total Gallons Pumped: Description
Visual Inspection (note any problems with the sys	tem): NOTE: This does not serve as a compliance inspection.
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in.	X Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in.	X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. X Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. X Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid	Capacity = Percent Sludge and Scum in Tank %
Scum Layer Effluent Sludge Layer	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.