

## GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location System Location	
Address 1025 Inches Tr RILS	Telephone Number
City Afton State MV Z	IP 5500/ Property ID No./GEO Code
Owner Dan Hernnynn Pumping Date 10/5/15	
Contractor	
Maintainer MEYER SEWER MPCA License N	o. 915 Telephone Number 651-459-016.
What was done to the system?	Report Liquid Capacity in Gallons
☐ Tank(s) Pumped ☐ Sludge and scum measured. Do tanks need to be pumped?	Tank 1: /Soa Pumped Tank 2: /coxxx Pumped  Tank 3: Pumped Tank 4: Pumped
Yes No (If no provide measurements below)	Total Gallons Pumped: 2500
Visual Inspection (note any problems with the system):	NOTE: This does not serve as a compliance inspection.
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped  Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. <b>X</b> Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total Sludg	ge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity	= Percent Sludge and Scum in Tank %
from	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.