

Signature

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location System Location	
Address April 14/89 Wh	S∠ ≤ Telephone Number
City Hastiles	State ///ZIP 55 @ Property ID No./GEO Code
Owner Charles Thompson	Pumping Date 10/5/15
Contractor	
Maintainer MEYER SEWER	MPCA License No. 915 Telephone Number 651-459-016.
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: Care Pumped Tank 2: Care Pumped
Sludge and scum measured. Do tanks need to be pumped?	Tank 3: Pumped Tank 4: Pumped
Yes No (If no provide measurements bel	Total Gallons Pumped: 2000
Visual Inspection (note any problems with the s	system): NOTE: This does not serve as a compliance inspection.
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width	in. X Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius	in. X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu, in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. X Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. X Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liqu	uid Capacity = Percent Sludge and Scum in Tank %
Scum Layer Scum Layer	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet
Effluent	Tank Depth measured from invert of outlet pipe to bottom of tank Tank Depth measured from invert of outlet than 25 percent of the tank's liquid capacity.
Sludge Layer	woman.

Date

Reset Form