

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

**GOVERNMENT CENTER** 

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## **SSTS MAINTENANCE REPORT**

System Location				
Address 9040	Green Cloud	Island Dr. S	Telephone Number	
City St.	Paul Park		Property ID No./GEO Code	
Owner amy Williams Pumping Date 5/1/15				
Contractor				
Maintainer MEYER SEWER MPCA License No. 915 Telephone Number 651-459-016				
What was done to the system?  Tank(s) Pumped Sludge and scum measured. Do tanks need to be pumped?  Yes No (If no provide measurements below)  Report Liquid Capacity in Gallons  Tank 1: /500 Pumped Tank 2: Pumped  Tank 3: Pumped  Total Gallons Pumped:				
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.				
		14		
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped				
Tank Length	in. <b>X</b> Tank Width	in. X Tank Depth in.	■ Tank Volume (cubic inches)	
Tank Radius	in. <b>X</b> Tank Radius	in. <b>X 3.14 =</b> Tank Volume (c	cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch				
Sludge Level	in. <b>X</b> Gallons Per Inch	= Sludge Volume Gal	llons	
Scum Level	in. <b>X</b> Gallons Per Inch	= Scum Volume Gal	llons	
Sludge Volume + Scum Volume = Total Sludge and Scum Volume Gallons				
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %				
Scum Layer			*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than  12 inches from the bottom of the outlet	
Effluent Sludge Layer		Tank Depth measured from invert of outlet pipe to bottom of tank	baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.	
Jidoge Layer			capacity.	
Signature		Date	Reset Form	