

Ca an

Signature

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location			
Address 16197	3rd St C+S.		Telephone Number
City Lakeland State MN ZIP 55043 Property ID No./GEO Code			
Owner Myon Nelson Pumping Date 6/2/15			
Contractor			
Maintainer MEYER SEWER MPCA License No. 915 Telephone Number 651-459-016			
What was	s done to the system?	Repor	t Liquid Capacity in Gallons
Tank(s) Pumped		Tank 1: 1250 Pumped Tank 2: 1250 Pumped	
			Pumped Tank 4: Pumped
Do tanks need to be pumped? Total Gallons Pumped: 2600			
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.			
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped			
Tank Length	in. X Tank Width in.)	Tank Depth in. =	Tank Volume (cubic inches)
Tank Radius	in. X Tank Radius in.	X 3.14 = Tank Volume (cubi	c inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch			
Sludge Level	in. X Gallons Per Inch =	Sludge Volume Gallon	<u> </u>
Scum Level	in. X Gallons Per Inch	Scum Volume Gallon	S
Sludge Volume		Total Sludge and Scum Volume	Gallons
			udge and Scum in Tank %
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %			
Scum Layer Effluent Sludge Layer		Tank Depth measured from invert of outlet pipe to bottom of tank	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.
		<u> </u>	

Date

Reset Form