

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
	AUE, N Telephone Number
Sin 1 Sin	m NZIP 55049 Property ID No./GEO Code
Owner Bizyan Pomeroy Pumping Date 6/8/15	
Maintainer MEVED CELLED MPCA License No. 915 Telephone Number 651-457-016	
Maintainer MEYER SEWER MPCAL	icense No. 915 Telephone Number 651-459-0163
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped 3	Tank 1: 1000 Pumped Tank 2: 1000 Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)	Total Gallons Pumped: 2000
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X	Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X	3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Tank Volume (cu. in.) / 231.01 = Liquid Cap	
Sludge Level in. X Gallons Per Inch = Sl	udge Volume Gallons
Scum Level in. X Gallons Per Inch = Sc	cum Volume Gallons
	otal Sludge and Scum Volume Gallons
Sludge Volume + Scum Volume = To	Stall Studge and Scum Volume
Total Słudge and Scum Volume / Liquid Capa	acity = Percent Sludge and Scum in Tank %
	*Tanks must be pumped if either of the
	following conditions exist:
Scum Layer	1. The top of the sludge layer is less than 12 inches from the bottom of the outlet
	Tank Depth measured baffle; or
Effluent	from invert of outlet 2. Total studge and scum volume is greater than 25 percent of the tank's liquid
Sludge Layer	pipe to bottom of tank capacity.
	1.61.
Signature //	Date 6/6/15 Reset Form