

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

5ystem I	ocation
Address 1/599 W Point Douglas	Rd. 5 Telephone Number
City Kastings State in N	ZIP55033 Property ID No./GEO Code
Owner Jim Haines Pumping Dat	e 7/6/15
Contractor /	
Maintainer MEYER SEWER MPCA License	No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: /500 Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)	Total Gallons Pumped: 1500
Visual Inspection (note any problems with the system):	NOTE: This does not serve as a compliance inspection.
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank D	Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14	= Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity	Gallons / Tank Depthin. = Gallons/Inch
Sludge Level in. X Gallons Per Inch = Sludge V	olume Gallons
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total Slu	dge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
	*Tanks must be pumped if either of the
	following conditions exist:
Scum Layer	1. The top of the sludge layer is less than 12 inches from the bottom of the outlet
	baffle; or printed baffle; or 2. Total sludge and scum volume is greater
	e to bottom of tank than 25 percent of the tank's liquid capacity.
Sladyc Luyci	
71	

Date