

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER
14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006
Office: 651-430-6655 TTY: 651-430-6246 FAX: 651-430-6730

Subsurface Sewage Treatment System Maintenance Permit

This section must be completed in its entirety to constitute a valid maintenance permit. This permit must be completed prior to performing maintenance activities and remain on-site for the duration of the maintenance activity.

Property Address:	Tank Me Liquid Level of Sludge Level in Sludge + Scumments) ments) Maintenance Hole Other Yes No	asurement (must be a Tank in Tank in Liquid cum Tank (enter authorization of the content of the cum and the cum in Tank in Tan	e completed if tanks I Scum Level in Tank Level X 100 anks must be pumped in the code of the	NOT pumped) in if 25% or greater NO Man hole
Maintenance Permit No: WJELL p13 Maintenance Performed Tank(s) Pumped Sludge and scum measured Do tanks need to be pumped? Yes No (if no provide measure) Access used to remove septage: A Were all covers securely replaced? 3. Is there evidence of tank leakage from evidence of damaged, cracked, or significant septic/Holding Tank Septic/Holding Tank	Tank Me Liquid Level of Sludge Level in Sludge + Scumments) ments) Maintenance Hole Other Yes No	and License No	e completed if tanks I Scum Level in Tank Level X 100 anks must be pumped in the code of the	in in if 25% or greater
Maintenance Performed Tank(s) Pumped Sludge and scum measured Do tanks need to be pumped? Yes No (if no provide measure) Access used to remove septage: Were all covers securely replaced? Were evidence of tank leakage from evidence of damaged, cracked, or significantly septic/Holding Tank Septic/Holding Tank	Tank Me Liquid Level of Sludge Level in Sludge + Scum = % Sludge & Sments) Maintenance Hole Other	asurement (must b f Tank in n Tank / Liquid cum / Tank (enter authorization of	Scum Level in Tank. Level X 100 anks must be pumped in the code of the	in in if 25% or greater
Tank(s) Pumped Sludge and scum measured Do tanks need to be pumped? Yes No (if no provide measure) Access used to remove septage: No Were all covers securely replaced? Is there evidence of tank leakage from evidence of damaged, cracked, or securely replaced. Tank Septic/Holding Tank Septic/Holding Tank	Liquid Level o Sludge Level in Sludge + Scum = % Sludge & S Maintenance Hole Other	f Tank in n Tank in class / Liquid focum 7 (enter authorization of	Scum Level in Tank. Level X 100 anks must be pumped in the pumped	in in if 25% or greater
Sludge and scum measured Do tanks need to be pumped? Yes No (if no provide measure) 1. Access used to remove septage: No 2. Were all covers securely replaced? 3. Is there evidence of tank leakage from evidence of damaged, cracked, or stank Tank Septic/Holding Tank Septic/Holding Tank	Sludge Level in Sludge + Scum = % Sludge & Sudge & Sud	n Tank in	Scum Level in Tank. Level X 100 anks must be pumped in the pumped	if 25% or greater n No Monhole
2. Were all covers securely replaced? (2) 3. Is there evidence of tank leakage from evidence of damaged, cracked, or significant terms of the secure of tank septic/Holding Tank septic/Holding Tank septic/Holding Tank	→ Yes □ No		U	
Tank Septic/Holding Tank Septic/Holding Tank	· · · · · · · · · · · · · · · · · · ·			
Septic/Holding Tank	Leaking Out	Leaking In	Cover Damage	v
	#1	☐ Yes ⊝ No	☐ Yes ₩o	
Pretreatment Tank	#2 ☐ Yes ☑ No	☐ Yes ☐No	☐ Yes (BNo	•
į.	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	
Pump Tank	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	
 4. How many gallons of septage were re Tank #1 750 gal Tank #2 75. 5. Other information: List any troublesh 	50 gal Pretreatme			

Meyer Sewer Service, Inc. 5325 Manning Ave S Afton, MN 55001

License# 915 P: 651-459-0162