Property address: 6507 Orchard Ridge Trail			Inspector initials/Date: ss   5/20/2019
1X 1			(mm/dd/yyyy)
4. Soil Separation - Compliance co	mpone	nt #4 of 5	
Date of installation: 6/1/1999 (mm/dd/yyyy)			Verification method(s):
Shoreland/Wellhead protection/Food beverage lodging?	☐ Yes	⊠ No	Soil observation does not expire. Previous soil observations by two independent parties are sufficient, unless site conditions have been altered or local
Compliance criteria:			requirements differ.
For systems built prior to April 1, 1996, and not located in Shoreland or Wellhead Protection Area or not serving a food, beverage or lodging establishment:	☐ Yes	□No	☐ Conducted soil observation(s) (Attach boring logs)
			☐ Not applicable (Holding tank(s), no drainfield)
Drainfield has at least a two-foot vertical separation distance from periodically saturated soil or bedrock.			Unable to verify (See Comments/Explanation)
			☑ Other (See Comments/Explanation)
Non-performance systems built April 1.		□No	Comments/Explanation:
1996, or later or for non-performance systems located in Shoreland or Wellhead Protection Areas or serving a food, beverage, or lodging establishment:			Attached soil verification from 2014 the last time the system was looked at. I also verified soil with a boring.
Drainfield has a three-foot vertical separation distance from periodically saturated soil or bedrock.*			
"Experimental", "Other", or "Performance" systems built under pre-2008 Rules; Type IV or V systems built under 2008 Rules (7080. 2350 or 7080.2400 (Advanced Inspector License required)	☐ Yes	□No	Indicate depths or elevations
			A Bottom of distribution media 15" - 23"
Drainfield meets the designed vertical			B. Periodically saturated soil/bedrock 60"
separation distance from periodically saturated soil or bedrock.			C. System separation 36"
Any "no" answer above indicates the system is failing to protect groundwater.			D. Required compliance separation* 36"  *May be reduced up to 15 percent if allowed by Local Ordinance
. a.m.g. to protest groundwater.			
5. Operating Permit and Nitrogen BMP* - Compliance component #5 of 5 Not applicable			
Is the system operated under an Operating I			☐ No If "yes", A below is required
Is the system required to employ a Nitrogen	BMP?		☐ No If "yes", B below is required
BMP = Best Management Practice(s) specified in the system design			
If the answer to both questions is "no", this section does not need to be completed.			
Compliance criteria			
Operating Permit number.			
Have the Operating Permit requiremen	ts been n	net?	☐ Yes ☐ No
b Is the required nitrogen BMP in place a			? Yes No
Any "no" answer indicates Noncompliance.			
Upgrade Requirements (Minn. Stat. § 115.55) An imminent threat to cubic health and safety (ITPHS) must be upgraded, colleged, as its use			

discontinued within ten months of receipt of this notice or within a shorter period if required by local ordinance. If the system is failing to protect ground water, the system must be upgraded, replaced, or its use discontinued within the time required by local ordinance. If an existing system is not failing as defined in law, and has at least two feet of design soil separation, then the system need not be upgraded, repaired, replaced, or its use discontinued, notwithstanding any local ordinance that is more strict. This provision does not apply to systems in shoreland areas, Wellhead Protection Areas, or those used in connection with food, beverage, and lodging establishments as defined in law.