

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 9830 55th St 11	Telephone Number
City Lake Elmo	State MM ZIP 5 50 42, Property ID No./GEO Code
Owner Phia Vane	Pumping Date 4/20/15 .
	Contractor
Maintainer MEYER SEWER	MPCA License No. 915 Telephone Number 651-459-016
What was done to the system? Tank(s) Pumped Sludge and scum measured. Do tanks need to be pumped? Yes No (If no provide measurements be Visual Inspection (note any problems with the section)	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches) Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches) Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. X Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. X Gallons Per Inch Sludge Volume + Scum Volume	= Scum Volume Gallons = Total Sludge and Scum Volume Gallons uid Capacity Percent Sludge and Scum in Tank %
Scum Layer Effluent Sludge Layer Signature	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity. Date *Reset Form