

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 16730 2Nd 57. S	Telephone Number
City Laks land Shones Statem	V ZIP5504/3 Property ID No./GEO Code
Owner Laurie Skelly Pumping	
Contractor	
Maintainer MEYER SEWER MPCALIC	ense No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 1200 Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)	Total Gallons Pumped: 1200
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection	
	·
**T	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Ta	nk Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Tota	I Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacit	= Percent Sludge and Scum in Tank
	*Tanks must be pumped if either of the
	following conditions exist: 1. The top of the sludge layer is less than
Scum Layer H	12 inches from the bottom of the outlet
Effluent	Tank Depth measured from invest of outlot 2. Total sludge and scum volume is greate
	pipe to bottom of tank than 25 percent of the tank's liquid
Sludge Layer	capacity.
	