

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

		System L	ocation			
Address / Bint Road			Telephone Number			
City Bay	port	State MN	ZIP 5500.3 Pro	pperty ID No./GEO Code		
Owner R&L	3 Schmidt	Pumping Date			**************************************	
		Contra				
Maintainer ME	ER SEWER	MPCA License	No. 915	Telephone Number 65/	459-016	
What	was done to the system?		Report Liquid Capacity in Gallons			
Prank(s) Pumped /			Tank 1: 1000 Pumped Tank 2: Pumper			
Sludge and scum measured.			Tank 3:	Pumped Tank 4:	Pumped	
Do tanks need to be pumped?  Yes No (If no provide measurements below)			Total Gallons Pumped: 1000			
	(note any problems with			es not serve as a complian	ace inspection	
			77012. 13773 00	cs from serve as a complain	- Inspection	
			•			
	*Tank Meas	urements-Use Only	/ If Tank(s) Were NO	「Pumped		
Tank Length	in. <b>X</b> Tank Width	in. <b>X</b> Tank D	epth in =	Tank Volume (cubic inches)	<del></del>	
Tank Radius	in. 🗶 Tank Radius	in. <b>X 3.14</b>	= Tank Volume (cub	pic inches)	<del></del>	
Tank Volume (cu, ir	 1.) / <b>231.01</b> =	Liquid Capacity	Gallons /	Tank Depth in. = Gallo	ns/Inch	
Sludge Level	in. <b>X</b> Gallons Per Inch	-			promise the state of the state	
		= Sludge V	***************************************			
Scum Level	in. <b>X</b> Gallons Per Inch	= Scum Vol	ume Gallo	ns		
Sludge Volume	+ Scum Volume	= Total Sluc	dge and Scum Volume	Gallons Gallons		
Total Sludge and Se	cum Volume /	Liquid Capacity	= Percent	Sludge and Scum in Tank	%	
-		F		*Tanks must be pumped if following conditions exist:		
P .				1. The top of the sludge lay		
Scum Layer				12 inches from the bottom	of the outlet	
Effluent		fron	k Depth measured n invert of outlet	baffle; or  2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.		
Sludge Layer		Pipe	e to bottom of tank			
	12/1			/		