

OOYLINIMEITI CEITTEN

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

	System Location
Address 1551 Quenth the	S Telephone Number
City St Croix Beach	State ZIP Property ID No./GEO Code
Owner George Front	Pumping Date 9/ds/15
,	Contractor
Maintainer MEYER SEWER	MPCA License No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 12 00 Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements be	Total Gallons Pumped: 12000
Visual Inspection (note any problems with the	system;. ROTE. This does not serve as a compliance inspection
*Tank Measure	nents-Use Only If Tank(s) Were NOT Pumped
Tank Length in. X Tank Width	in. X Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius	in. X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Li	quid Capacity Gallons / Tank Depth in. = Gallons/Inch
Sludge Level in. X Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. X Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	— Total Studge and Scuri Volume
Total Sludge and Scum Volume / Lie	quid Capacity = Percent Sludge and Scum in Tank %
Scum Layer Effluent Sludge Layer	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greated than 25 percent of the tank's liquid capacity.