

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		System Location		
Address //875	122nd St Ch S	7	Telephone Number	
City Hastings	,	State NN ZIP 55033 Pro	perty ID No./GEO Code	
Owner Shawn	Bushinski	Pumping Date /1/1//	-	
		Contractor		
Maintainer MEY	ER SEWER	MPCA License No. 915	Telephone Number 65/-459-016	
What was done to the system?		Repo	Report Liquid Capacity in Gallons	
🔀 Tank(s) Pumped		Tank 1: ISag	Tank 1: 1500 Pumped Tank 2: 1000 Pumper	
Sludge and scum measured.			Pumped Tank 4; Pumped	
Do tanks need to be pumped? Yes No (If no provide measurements below)			Total Gallons Pumped: 2500	
Visual Inspection (note any problems with the system):		system): NOTE: This doe	NOTE: This does not serve as a compliance inspection	
	*Tank Measure	ments-Use Only If Tank(s) Were NOT	Pumped	
Tank Length	in. X Tank Width		Tank Volume (cubic inches)	
Tank Radius	in. X Tank Radius	in. X 3.14 = Tank Volume (cub		
·	•••			
Tank Volume (cu. in.)) / 231.01 = Li	quid Capacity Gallons /	Tank Depth in. = Gallons/Inch	
Sludge Level	in. X Gallons Per Inch	= Sludge Volume Gallo	ns	
Scum Level	in. X Gallons Per Inch	= Scum Volume Gallo	ns	
Sludge Volume	+ Scum Volume	= Total Sludge and Scum Volume	Gallons	
Total Sludge and Scu	um Volume / Lic	uid Capacity = Percent S	Sludge and Scum in Tank%	
			*Tanks must be pumped if either of the	
		Ħ	following conditions quiets	
Course			following conditions exist: 1. The top of the sludge layer is less than	
Scum Løyer			 The top of the sludge layer is less than inches from the bottom of the outlet 	
Scum Layer Effluent		Tank Depth measured from invert of outlet	1. The top of the sludge layer is less than	