

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

1

2212	MAINTENANCE REPORT
	System Location
Address 13535 33RCl s	Telephone Number
city Afton	State MIN ZIP5500/ Property ID No./GEO Code
Owner Dak Jackson	Pumping Date 10/26/15
	Contractor
Maintainer MEYER SEWER	MPCA License No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped 2	Tank 1: 1000 Pumped Tank 2: 1000 Pumper
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements)	Total Gallons Pumped: 2000
Visual Inspection (note any problems with th	
The state of the s	
	The state of the s
	162 L 1 145
*Tank Measur	ements-Use Only If Tank(s) Were NOT Pumped
Tank Length in. X Tank Width	in. X Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius	in. X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = 1	iquid Capacity Gallons / Tank Depth in. = Gallons/Inch
Sludge Level in. X Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. X Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume Gallons
	quid Capacity = Percent Sludge and Scum in Tank %
Total stage that sealing voids he	Telegrand search in terms
	*Tanks must be pumped if either of the following conditions exist:
	1. The top of the sludge layer is less than
Scum Layer	12 inches from the bottom of the outlet baffle; or
Effluent	from invest of cutlet 2. Total sludge and scum volume is greate
Sludge Layer	pipe to bottom of tank than 25 percent of the tank's liquid capacity.
Jacob Carlos	