

(Suplicate?)

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

	5515 MAINTENANCE REPORT
	Systemilocation
Address /) 79	5 OZa-K TNN Telephone Number
City Stillus	5. June 10 No /GFO Code
Owner Sudi P	
	Contractor
Maintainer ()/500	ns sewer MPCA License No. Telephone Number 65-1-464-16
Tank(s) Pumped Sludge and scum r Do tanks need to b	be pumped?  (If no provide measurements below)  Total Gallons Pumped:
Visual Inspection (/	note any problems with the system): NOTE: This does not serve as a compliance inspecti
	*Tank Measurements-Use Only If Tank(s) Were NOT Pumped
Tank Length	in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)
Tank Radius	in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.)	
Sludge Level	in. <b>X</b> Gallons Per Inch = Sludge Volume Gallons
Scum Level	in. X Gallons Per Inch = Scum Volume Gallons
Sludge Volume	+ Scum Volume = Total Sludge and Scum Volume Gallons
Total Sludge and Scu	
Scum Layer Effluent Sludge Layer	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less that 12 inches from the bottom of the outled baffle; or  2. Total sludge and scum volume is great than 25 percent of the tank's liquid capacity.
Signature 2	Date 12-2-15 Reset Form